Data Sheet No. PD60294

International
IOR Rectifier

IRS21853SPBF

DUAL HIGH SIDE DRIVER IC

Features

- Gate drive supply range from 10 V to 20 V
- Under voltage lockout for V_{CC} & $V_{BS1,2}$
- 5 V input logic compatible
- Tolerant to negative transient voltage
- Matched propagation delays for all channels
- RoHS compliant

Descriptions

The IRS21853 is a high voltage, high speed power MOSFET and IGBT dual high-side driver with propagation delay matched output channels. Proprietary HVIC and latch immune CMOS technologies enable ruggedized monolithic construction. The floating logic input is compatible with standard CMOS or LSTTL output, down to 3.3 V logic and can be operated up to 600 V above the ground. The output driver features a high pulse current buffer stage designed for minimum driver cross-conduction. The floating channel can be used to drive an N-channel power MOSFET or IGBT in the high-side configuration, which operates up to 600 V.

Product Summary


V_{OFFSET}	600 V max
V_{OUT}	10 V to 20 V
t_{on}/t_{off} (typ)	170 ns/170 ns
$I_{o+/-}$	2 A/2 A
Delay Matching	40 ns

Package




16-Lead SOIC (narrow body)

Typical Connection Diagram



Typical Connection Diagram for ER Circuit in PDP



Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM.

Symbol	Definition	Min	Max	Units
V_{CC}	Low side supply voltage	-0.3	20 (Note1)	V
V_{IN}	Logic input voltage (HIN1,2)	COM-0.3	V_{CC} +0.3	
$V_{B1,2}$	High side floating well supply voltage	-0.3	620 (Note1)	
$V_{S1,2}$	High side floating well supply return voltage	$V_{B1,2}$-20	V_{Bn}+0.3	
$V_{HO1,2}$	Floating gate drive output voltage	$V_{S1,2}$-0.3	V_{Bn}+0.3	
dV_S/dt	Allowable $V_{S1,2}$ offset supply transient relative to COM	-	50	V/ns
P_D	Package power dissipation @ $T_A \leq$+25 ºC	-	1.25	W
$R_{\theta JA}$	Thermal resistance, junction to ambient	-	100	ºC/W
T_J	Junction temperature	-55	150	ºC
T_S	Storage temperature			
T_L	Lead temperature (soldering, 10 seconds)	-	300	

Note1: All supplies are fully tested at 25 V. An internal 20 V clamp exists for each supply.

Recommended Operating Conditions

For proper operation, the device should be used within the recommended conditions. All voltage parameters are absolute voltages referenced to COM. The offset rating are tested with supplies of (V_{CC}-COM)=($V_{B1,2}$-$V_{S1,2}$)=15 V.

Symbol	Definition	Min	Max	Units
V_{CC}	Low side supply voltage	10	20	V
V_{IN}	HIN1, 2 input voltage	COM	VCC	
$V_{B1,2}$	High side floating well supply voltage	$V_{S1,2}$+10	$V_{S1,2}$+20	
$V_{S1,2}$	High side floating well supply offset voltage	Note 2	600	
$V_{HO1,2}$	Floating gate drive output voltage	$V_{S1,2}$	$V_{B1,2}$	
T_A	Ambient temperature	-40	125	ºC

Note 2: $V_{S1,2}$ and $V_{B1,2}$ voltages will be tolerant to short negative transient spikes. These will be defined and specified in the future.

Note 3: Logic operation for V_S of –5 V to 600 V. Logic state held for V_S of –5 V to $-V_{BS1,2}$. (Please refer to Design Tip DT97-3 for more details).

Static Electrical Characteristics

(V_{CC}-COM)=($V_{B1,2}$-$V_{S1,2}$)=15 V. T_A = 25 °C unless otherwise specified. The V_{IN}, $V_{IN,TH}$, and I_{IN} parameters are referenced to COM. The V_O and I_O parameters are referenced to respective $V_{S1,2}$ and are applicable to the respective output leads HO1,2. The V_{CCUV} parameters are referenced to COM. The $V_{BSUV1,2}$ parameters are referenced to $V_{S1,2}$.

Symbol	Definition	Min	Typ	Max	Units	Test Conditions
V_{CCUV+}	V_{CC} supply undervoltage positive going threshold	8.0	8.9	9.8	V	
V_{CCUV-}	V_{CC} supply undervoltage negative going threshold	7.4	8.2	9.0		
V_{BSUV+}	$V_{BS1,2}$ supply undervoltage positive going threshold	8.0	8.9	9.8		
V_{BSUV-}	$V_{BS1,2}$ supply undervoltage negative going threshold	7.4	8.2	9.0		
$I_{LK1,2}$	High-side floating well offset supply leakage current	---	---	50	µA	$V_{B1,2}$ = $V_{S1,2}$ = 600 V
I_{QBS}	Quiescent V_{BS} supply current	---	75	150		HIN1,2 = 0 V or 5 V
I_{QCC}	Quiescent V_{CC} supply current	---	110	220		
V_{IH}	Logic “1” input voltage	3.5	---	---	V	
V_{IL}	Logic “0” input voltage	---	---	0.6		
V_{OH}	HO1,2 high level output voltage, V_{BIAS}-V_O	---	---	1.4		I_o= 0 A
V_{OL}	HO1,2 low level output voltage, V_O	---	---	0.06		I_o=20 mA
I_{IN+}	Logic “1” input bias current	---	5	20	µA	$V_{HIN1,2}$=5 V
I_{IN-}	Logic “0” input bias current	---	---	5		$V_{HIN1,2}$=0 V
I_{o+}	Output high short circuit pulsed current HO1,2	---	2	---	A	V_O=0 V,V_{IN}=0 V, PW<=10 µs
I_{o-}	Output low short circuit pulsed current HO1,2	---	2	---		V_O=15 V,V_{IN}=5 V, PW<=10 µs


Dynamic Electrical Characteristics (All values are target data)

(V_{CC}-COM)= ($V_{B1,2}$-$V_{S1,2}$)=15 V. T_A = 25 ^oC unless otherwise specified. C_L = 1000 pF unless otherwise specified. All parameters are reference to COM.

Symbol	Definition	Min	Typ	Max	Units	Test Conditions
t_{on}	Turn-on propagation delay (HO1,2)	---	170	---	ns	($V_{s1,2}$-COM)=0 V
t_{off}	Turn-off propagation delay (HO1,2)	---	170	---		($V_{s1,2}$-COM)=600 V
t_r	Turn-on rise time	---	15	50		
t_f	Turn-off fall time	---	15	50		
MT	Delay matching (Note 1)	---	---	40		

Note 4:Max($t_{on,HO1}$, $t_{on,HO2}$)- Min($t_{on,HO1}$, $t_{on,HO2}$); Max($t_{off,HO1}$, $t_{off,HO2}$)- Min($t_{off,HO1}$, $t_{off,HO2}$)


Functional Block Diagram



Lead Definitions

Symbol	Description
VCC	Low side supply voltage
COM	Ground
VB1,2	High side gate drive floating supply
HO1,2	High side driver outputs
VS1,2	High voltage floating supply return
HIN1,2	Logic inputs for high side gate driver outputs (in phase)

Lead Assignments






Figure 1: Switching Time Waveforms




Figure 2: Input/Output Timing Diagram




Figure 3A. Turn-On Time vs. Temperature




Figure 3B. Turn-On Time vs. Supply Voltage




Figure 4A. Turn-Off Time vs. Temperature




Figure 4B. Turn-Off Time vs. Supply Voltage




Figure 5A. Turn-On Rise Time vs.Temperature




Figure 5B. Turn-On Rise Time vs. Supply Voltage




Figure 6A. Turn-Off Fall Time vs. Temperature




Figure 6B. Turn-Off Fall Time vs. Supply Voltage




Figure 7A. Logic "1" Input Voltage vs. Temperature




Figure 7B. Logic "1" Input Voltage vs. Supply Voltage




Figure 8A. Logic "0" Input Voltage vs. Temperature




Figure 8B. Logic "0" Input Voltage vs. Supply Voltage




Figure 9A. High Level Output vs. Temperature




Figure 9B. High Level Output vs. Supply Voltage




Figure 10A. Low Level Output vs.Temperature




Figure 10B. Low Level Output vs. Supply Voltage




Figure 11A. Offset Supply Leakage Current vs. Temperature




Figure 11B. Offset Supply Leakage Current vs. Supply Voltage




Figure 12A. V_{BS} Supply Current vs. Temperature




Figure 12B. V_{BS} Supply Current vs. Supply Voltage




Figure 13A. V_{cc} Supply Current vs. Temperature




Figure 13B. V_{cc} Supply Current vs. Supply Voltage




Figure 14A. Logic "1" Input Current vs. Temperature




Figure 14B. Logic "1" Input Current vs. Supply Voltage




Figure 15A. Logic "0" Input Current vs. Temperature




Figure 15B. Logic "0" Input Current vs. Supply Voltage




Figure 16. V_{cc} Undervoltage Threshold (+) vs. Temperature




Figure 17. V_{cc} Undervoltage Threshold (-) vs. Temperature




Figure 18. V_{BS} Undervoltage Threshold (+) vs. Temperature




Figure 19. V_{BS} Undervoltage Threshold (-) vs. Temperature




Figure 20A. Output Source Current vs. Temperature




Figure 20B. Output Source Current vs. Supply Voltage




Figure 21A. Output Sink Current vs.Temperature




Figure 21B. Output Sink Current vs. Supply Voltage






Figure 22. Maximum V_S Negative Offset vs. Supply Voltage



NOTES:


1. DIMENSIONING & TOLERANCING PER ANSI Y14.5W-1982
2. CONTROLLING DIMENSION. MILLIMETER
3. DIMENSIONS ARE SHOWN IN MILLIMETER [INCHES]
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AC
5. DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE
6. DIMENSION DOES NOT INCLUDE MOLD PROTUSIONS. MOLD PROTUSIONS SHALL NOT EXCEED 0.15 [.006]

16-Lead SOIC (narrow body)



CARRIER TAPE DIMENSION FOR 16SOICN


Code	Metric		Imperial	
	Min	Max	Min	Max
A	7.90	8.10	0.311	0.318
B	3.90	4.10	0.153	0.161
C	15.70	16.30	0.618	0.641
D	7.40	7.60	0.291	0.299
E	6.40	6.60	0.252	0.260
F	10.20	10.40	0.402	0.409
G	1.50	n/a	0.059	n/a
H	1.50	1.60	0.059	0.062



REEL DIMENSIONS FOR 16SOICN

Code	Metric		Imperial	
	Min	Max	Min	Max
A	329.60	330.25	12.976	13.001
B	20.95	21.45	0.824	0.844
C	12.80	13.20	0.503	0.519
D	1.95	2.45	0.767	0.096
E	98.00	102.00	3.858	4.015
F	n/a	22.40	n/a	0.881
G	18.50	21.10	0.728	0.830
H	16.40	18.40	0.645	0.724

LEAD-FREE PART MARKING INFORMATION



?	MARKING CODE
P	Lead Free Released
	Non-Lead Free Relased

ORDER INFORMATION

16-Lead SOIC IRS21853SPBF

16-Lead SOIC Tape & Reel IRS21853STRPBF