



1. Mechanical Dimensions:




Suggested Pad Layout

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. All listed parameters are to be within tolerance from -40°C to +125°C unless otherwise noted
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: $\pm 0.004'' (0.102\text{mm})$
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Outsourced item processed & controlled under XFMRs QA system

2. Schematic:



3. Electrical Specification: @25°C

INDUCTANCE: 538nH $\pm 5\%$

Q: 87 Min

TEST FREQ: 50MHz

DCR: 90.0 mOhms Max

Rated Current: 2.0A Max

SRF: 490MHz Min

DOC REV.: A/2

XFMRs Inc. www.XFMRs.com	Title: Micro Spring Air Core Inductors		
	UNLESS OTHERWISE SPECIFIED TOLERANCES: .xxx ± 0.25 Dimensions in mm	P/N: XF132-20SM DWN.	Xiang
SHEET 1 OF 1	APP.	YK Liao	Aug-08-16

PROPRIETARY

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization.