



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

KBJL10005G THRU KBJL1010G

Features


- Halogen free available upon request by adding suffix "-HF"
- Diffused Junction
- Low Forward Voltage Drop
- High Current Capability
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1
- Lead Free Finish/RoHS Compliant (NOTE 1) ("P" Suffix designates RoHS Compliant. See ordering information)

Maximum Ratings

- Operating Junction Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- UL Recognized File # E165989

MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
KBJL10005G	KBJL10005G	50V	35V	50V
KBJL1001G	KBJL1001G	100V	70V	100V
KBJL1002G	KBJL1002G	200V	140V	200V
KBJL1004G	KBJL1004G	400V	280V	400V
KBJL1006G	KBJL1006G	600V	420V	600V
KBJL1008G	KBJL1008G	800V	560V	800V
KBJL1010G	KBJL1010G	1000V	700V	1000V

10 Amp GLASS PASSIVATED BRIDGE RECTIFIERS 50 to 1000 Volts




Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	10A	$T_C = 100^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	180A	8.3ms, half sine
Maximum Forward Voltage Drop Per Element	V_F	1.1V	$I_{FM} = 5.0\text{A}$ per element; $T_A = 25^\circ\text{C}$ (Note 2)
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	5 μA	$T_A = 25^\circ\text{C}$
I^2t Rating for fusing	I^2t	60A ² S	($t < 8.3\text{ms}$)

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7
2. Pulse Test: Pulse Width 300usec, Duty Cycle 1%

DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.972	.996	24.70	25.30	
B	.394	.417	10.00	10.60	
C	.697	.736	17.70	18.70	
D	.142	.157	3.60	4.00	
E	.110	.126	2.80	3.20	
F	.217	.232	5.50	5.90	
G	.122	.134	3.10	3.40	
H	.669 typ		1.70 typ		
I	.035	.043	0.90	1.10	
J	.098	.114	2.50	2.90	
K	.016	.024	0.40	0.60	
L	.287	.303	7.30	7.70	



www.mccsemi.com



Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-BP	Bulk;2.4K/Ctn

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com