ADELS contact

## PCB Connectors

# GSK 820 H/ 2



Terminal Block Horizontal, Pin Spacing: 5.0 mm, 2 pole, Insulating Material: PBT, Voltage Rating: 250 V, Current Rating: 15 A, Cross-Section: 1.5 mm²

## Order Info

| | |
|---|---|
| **Reference Number (ref. no.)** | 324402 |
| **Applications** | Lighting, Electrical Appliances, Transformers, Electronics |
| **PU** | 1,000 |
| **EAN** | 4028012109401 |

## Type

| | |
|---|---|
| **Type** | Terminal Block Horizontal |
| **Number of poles** | 2 pole |
| **Clamping Units per Pole** | 1 |
| **Colour** | blue |
| **Cross-Section** | 1.5 mm² |
| **Connection Type** | Screw |

## Technical Data

| | |
|---|---|
| **Voltage Rating** | 250 V |
| **Current Rating** | 15 A |
| **Insulating Material** | PBT |
| **Contact Material** | Brass |
| **Core Cross-Section min.** | 0.5 mm² |
| **Core Cross-Section max.** | 2.5 mm² |
| **Flammability Rating** | V-0 |
| **max. Ambient Temperature Operation** | 85 °C |
| **Type of Conductor Solid** | yes |
| **Type of Conductor Flexible** | yes |
| **Type of Conductor Stranded** | yes |
| **Stripping Length** | 4.5-5.0 mm |
| **Assembly Contact Screw** | 0.6x3.5 / ↻ 0.5 Nm |
| **Pin Spacing** | 5.0 mm |
| **Approbation EN60998** | GSK820_EN60998_20070920_VDE_40022167_web.pdf |
| **Approbation UL** | GSK820_GSK830_19890613_19961122_UL_E63492_1-09_Descripti |
| **Approbation CSA** | GSK_GST_Printklemmen_Serie_20160404_CSA_70070893_Certificat |