

# 3M™ Polyurethane Protective Tape 8545 Matte Black (no adhesive)

## Technical Data Sheet

### Product Description

3M™ Polyurethane Protective Tape 8545 Matte Black is made from an abrasion- resistant polyurethane elastomer that resists punctures, tearing, abrasion and erosion. It is formulated for resistance to ultraviolet light. When used in conjunction with an applied paste or structural adhesive, 3M 8545 Matte Black Tape provides protection of a surface from corrosion, abrasion and minor impact damage. It can be painted or applied over painted surfaces.

### Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes. ASTM = American Society for Testing and Materials. Metric values are listed in parenthesis.

#### A. Dimensions:

Approximate Tape Thickness:	0.04 inch (1.02 mm)
Standard Roll Length:	36 yd (32.9 m)
Available Widths:	1/2-inch min. to 24-inch max. (1.25 cm to 61 cm)
Approximate Weight:	1.98 lb/yd <sup>2</sup> (1.07 kg/m <sup>2</sup> )

#### B. Typical Physical Properties and Performance Characteristics:

PROPERTY	TEST METHOD	UNITS	TYPICAL VALUE
Tensile Strength @ Break	ASTM D882	lb/in (N/100 mm)	170 (2,975)
Elongation % @ Break	ASTM D882	%	500

### General Information

- 3M Polyurethane Protective Tape and Films have weather resistance properties and have been used to isolate and protect substrates from environmental damage and corrosive elements.
- 3M Polyurethane Protective Tape and Films may be painted per 3M Technical Bulletin, "Polyurethane Protective Tape, Painting Instructions" (70-0702-6358-0).

**Shipping and Storage**

No special/hazardous labeling or packaging required and no regulations for air, ground or water shipment for this product. Keep film in a clean area, away from excessive moisture and out of direct sunlight. Store rolls in the shipping carton. Return partially used rolls to the shipping carton. Shelf Life: Two (2) years from the date of manufacture or as expressly certified by 3M.

**Precautionary Information**

Refer to Product Label and Safety Data Sheet (SDS) for health and safety information before using this product. Always wear personal protection equipment, such as half or full face piece air purifying respirator suitable for organic vapors and particulates. For additional health and safety information, please visit [www.3m.com/MSDS](http://www.3m.com/MSDS) or call 1-800-364-3577 or (651) 737-6501.

**Additional Information**

In the U.S. call toll free 1-800-235-2376, or fax 1-800-435-3082 or 651-737-2171. For U.S. Military, call 1-866-556-5714. If you are outside of the U.S., please contact your nearest 3M representative.

**Authorization to Use**

Ensure products meet all applicable specifications, standards, and maintenance manual requirements for the platform being worked on and validate all aircraft approvals against current technical document.



*These products are manufactured under a 3M Quality Management System registered to the AS9100 standard*

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Automotive & Aerospace Solutions Division  
3M Center  
St. Paul, MN 55144-1000  
Phone 1-800-328-1684  
Web [www.3M.com/aerospace](http://www.3M.com/aerospace)

Issue date: 4/2020

3M is a trademark of 3M Company.  
All other trademarks are the property of their respective owners.  
© 3M 2020. All rights reserved.

