



# IME08-03BPOZW2K

IME

**INDUCTIVE PROXIMITY SENSORS**

**SICK**  
Sensor Intelligence.



### Ordering information

| Type            | Part no. |
|-----------------|----------|
| IME08-03BPOZW2K | 1074008  |

Other models and accessories → [www.sick.com/IME](http://www.sick.com/IME)

Illustration may differ



### Detailed technical data

#### Features

|                                            |                           |
|--------------------------------------------|---------------------------|
| <b>Housing</b>                             | Cylindrical thread design |
| <b>Housing</b>                             | Short-body                |
| <b>Thread size</b>                         | M8<br>1                   |
| <b>Diameter</b>                            | Ø 8 mm                    |
| <b>Sensing range <math>S_n</math></b>      | 3 mm                      |
| <b>Safe sensing range <math>S_a</math></b> | 2.43 mm                   |
| <b>Installation type</b>                   | Quasi-flush               |
| <b>Switching frequency</b>                 | 1,000 Hz                  |
| <b>Connection type</b>                     | Cable, 3-wire, 2 m        |
| <b>Switching output</b>                    | PNP                       |
| <b>Output function</b>                     | NC                        |
| <b>Electrical wiring</b>                   | DC 3-wire                 |
| <b>Enclosure rating</b>                    | IP67 <sup>1)</sup>        |
| <b>Special features</b>                    | Triple sensing range      |

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

|                            |                       |
|----------------------------|-----------------------|
| <b>Supply voltage</b>      | 10 V DC ... 30 V DC   |
| <b>Ripple</b>              | ≤ 10 %                |
| <b>Voltage drop</b>        | ≤ 2 V <sup>1)</sup>   |
| <b>Current consumption</b> | ≤ 10 mA <sup>2)</sup> |

<sup>1)</sup> At  $I_a$  max.

<sup>2)</sup> Without load.

<sup>3)</sup>  $U_b$  and  $T_a$  constant.

<sup>4)</sup> Of  $S_r$ .

|                                             |                                   |
|---------------------------------------------|-----------------------------------|
| <b>Time delay before availability</b>       | ≤ 50 ms                           |
| <b>Hysteresis</b>                           | 1 % ... 15 %                      |
| <b>Reproducibility</b>                      | ≤ 5 % <sup>3) 4)</sup>            |
| <b>Temperature drift (of S<sub>r</sub>)</b> | ± 10 %                            |
| <b>EMC</b>                                  | According to EN 60947-5-2         |
| <b>Continuous current I<sub>a</sub></b>     | ≤ 200 mA                          |
| <b>Current consumption, no load</b>         | ≤ 10 mA                           |
| <b>Cable material</b>                       | PVC                               |
| <b>Short-circuit protection</b>             | ✓                                 |
| <b>Reverse polarity protection</b>          | ✓                                 |
| <b>Power-up pulse protection</b>            | ✓                                 |
| <b>Shock and vibration resistance</b>       | 30 g, 11 ms/10 Hz ... 55 Hz, 1 mm |
| <b>Ambient operating temperature</b>        | -25 °C ... +75 °C                 |
| <b>Ambient storage temperature</b>          | -25 °C ... +75 °C                 |
| <b>Housing material</b>                     | Metal, Nickel-plated brass        |
| <b>Sensing face material</b>                | Plastic, Plastic                  |
| <b>Housing length</b>                       | 43 mm                             |
| <b>Thread length</b>                        | 25 mm                             |
| <b>Tightening torque, max.</b>              | ≤ 5 Nm                            |
| <b>UL File No.</b>                          | NRKH.E181493                      |

1) At I<sub>a</sub> max.

2) Without load.

3) U<sub>b</sub> and T<sub>a</sub> constant.

4) Of S<sub>r</sub>.

## Reduction factors

|                                   |                                                |
|-----------------------------------|------------------------------------------------|
| <b>Note</b>                       | The values are reference values which may vary |
| <b>St37 steel (Fe)</b>            | Approx. 1                                      |
| <b>Stainless steel (V2A, 304)</b> | Approx. 0.75                                   |
| <b>Aluminum (Al)</b>              | Approx. 0.46                                   |
| <b>Copper (Cu)</b>                | Approx. 0.42                                   |
| <b>Brass (Br)</b>                 | Approx. 0.56                                   |

## Installation note

|               |                                       |
|---------------|---------------------------------------|
| <b>Remark</b> | Associated graphic see "Installation" |
| <b>A</b>      | 3 mm                                  |
| <b>B</b>      | 20 mm                                 |
| <b>C</b>      | 8 mm                                  |
| <b>D</b>      | 9 mm                                  |
| <b>E</b>      | 1 mm                                  |
| <b>F</b>      | 30 mm                                 |


## Classifications

|                   |          |
|-------------------|----------|
| <b>ECI@ss 5.0</b> | 27270101 |
|-------------------|----------|

|                       |          |
|-----------------------|----------|
| <b>ECl@ss 5.1.4</b>   | 27270101 |
| <b>ECl@ss 6.0</b>     | 27270101 |
| <b>ECl@ss 6.2</b>     | 27270101 |
| <b>ECl@ss 7.0</b>     | 27270101 |
| <b>ECl@ss 8.0</b>     | 27270101 |
| <b>ECl@ss 8.1</b>     | 27270101 |
| <b>ECl@ss 9.0</b>     | 27270101 |
| <b>ETIM 5.0</b>       | EC002714 |
| <b>ETIM 6.0</b>       | EC002714 |
| <b>UNSPSC 16.0901</b> | 39122230 |


## Installation note

Quasi-flush installation




## Connection diagram

cd-003



## Dimensional drawing (Dimensions in mm (inch))

IME08 Short-body housing, cable, flush



- ① Connection
- ② Indication LED
- ③ Fastening nuts (2x); width across 13, metal

## Recommended accessories

Other models and accessories → [www.sick.com/IME](http://www.sick.com/IME)

|                                                                                     | Brief description                                                                                                                                                                   | Type               | Part no. |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------|
| Universal bar clamp systems                                                         |                                                                                                                                                                                     |                    |          |
|    | Universal bar clamp for mounting bars with 12 mm diameter, Zinc diecast, without mounting plate and screws                                                                          | BEF-KHS-KH3        | 5322626  |
| Mounting brackets and plates                                                        |                                                                                                                                                                                     |                    |          |
|    | Mounting plate for M8 sensors, steel, zinc coated, without mounting hardware                                                                                                        | BEF-WG-M08         | 5321722  |
|    | Mounting bracket for M8 sensors, steel, zinc coated, without mounting hardware                                                                                                      | BEF-WN-M08         | 5321721  |
| Terminal and alignment brackets                                                     |                                                                                                                                                                                     |                    |          |
|    | Clamping block for round sensors M8, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included                                                         | BEF-KH-M08         | 2051477  |
|                                                                                     | Clamping block for round sensors M8, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included                                                            | BEF-KHF-M08        | 2051478  |
| Plug connectors and cables                                                          |                                                                                                                                                                                     |                    |          |
|    | Head A: female connector, M12, 5-pin, straight, A-coded<br>Head B: open cable ends<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 2 m                              | YF2A15-020UB5XLEAX | 2095617  |
|  | Head A: female connector, M12, 4-pin, straight, A-coded<br>Head B: male connector, M8, 4-pin, straight, A-coded<br>Cable: Sensor/actuator cable, PUR, halogen-free, unshielded, 2 m | YF2A14-020UA3M8U14 | 2096112  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)