

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0757059103

Status: Active

Overview: GbX I-Trac™ Backplane Connector System

Description: GbX I-Trac™ Vertical Header Module, 1.85mm by 3.70mm Pitch, Right Guide, Left Endwall, 11 Rows, 10 Columns, 220 Circuits, Mating Pin Length 4.70mm

Documents:

[3D Model](#) [Packaging Specification PK-70873-587 \(PDF\)](#)

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

[Product Specification PS-75710-999 \(PDF\)](#)

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series 75705

Application Backplane, Midplane, Orthogonal

Component Type PCB Header

Overview GbX I-Trac™ Backplane Connector System

Product Name GbX I-Trac™

UPC 800756720098

Physical

Circuits (Loaded) 220

Circuits (maximum) 220

Color - Resin Black

Durability (mating cycles max) 200

First Mate / Last Break No

Flammability 94V-0

Guide to Mating Part Yes

Keying to Mating Part None

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold

Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 11.273/g

Number of Columns 10

Number of Pairs 6, Open Pin Field

Number of Rows 11

Orientation Vertical

PC Tail Length 2.10mm

PCB Locator No

PCB Retention Yes

PCB Thickness - Recommended 1.60mm

Packaging Type Tray

Pitch - Mating Interface 1.85mm, 3.70mm

Pitch - Termination Interface 1.00mm, 2.70mm

Plating min - Mating 0.762µm

Plating min - Termination 0.762µm

Polarized to PCB No


Stackable No

Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -55°C to +80°C

Termination Interface: Style Through Hole - Compliant Pin

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per
-ED/79/2015 (17
December 2015)

Halogen-Free

Status

Low-Halogen

Need more information on product
environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any
non-product compliance questions.

China ROHS
ELV

Green Image
Not Relevant

Search Parts in this Series

75705 Series

Mates With

75710 GbX I-Trac™ Right Angle Receptacle
Module

Use With

78232 GbX I-Trac™ Vertical Power
Receptacle. 75234 Backplane Free Standing
Guide Pin

Application Tooling | FAQ

Tooling specifications and manuals are
found by selecting the products below.
Crimp Height Specifications are then
contained in the Application Tooling
Specification document.

Global

Description

Product #

Current - Maximum per Contact	1.0A	Press-In Tool for <u>0622018603</u>
Data Rate	12.0 Gbps	Vertical Header 11-
Real Signals (per 25mm)	148	Row, 10-Column
Shield Type	N/A	Backplane Insertion <u>0621005110</u>
Shielded	No	Tool for Signal
Voltage - Maximum	120V AC (RMS)/DC	Contact Insertion
Solder Process Data		
Lead-freeProcess Capability	N/A	
Material Info		
Reference - Drawing Numbers		
Packaging Specification	PK-70873-587	
Product Specification	PS-75710-999	
Sales Drawing	SD-75705-004	

This document was generated on 06/10/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION