



Data sheet | Item number: 762-4101

Touch Panel 600; 10.9 cm (4.3"); 480 x 272 pixels; 2 x USB, 2 x ETHERNET;
Web Panel



www.wago.com/762-4101



Item description

PIO1 hardware configuration

- 2 x ETHERNET port for connecting to field devices and the engineering tool
- 2 x USB port for optional connection of a USB stick, mouse or keyboard

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Data

Technical data

Display diagonal	10.9 cm (4.3 Inches)
Display	Resistive touchscreen
Display colors	16 million colors
Graphics resolution	(480 x 272) px
Contrast ratio	600:1
Viewing angle (horizontal/vertical)	80° / 80°
Brightness	500 cd/m ²
Visualization	Webserver
ETHERNET protocols	DHCP DNS FTP FTPS HTTP HTTPS SSH
Communication	Web browser (HTML5)
Operating system	Real-time Linux (with RT-Preempt patch)
Processor	ARM [®] Cortex [®] A9 Quadcore 1.0 GHz
Main memory (RAM)	2,048 MB
Internal memory (flash)	4096 MB
Memory card type	microSD (max. 2 GB); microSDHC (max. 32 GB)
Indicators	Three-color LED (red, green, blue)
Controls	Resistive touch panel; 2 capacitive keys; proximity sensor
Supply voltage	24 VDC, SELV (18 ... 31.2 V); with reverse voltage protection
Operating power	5.8 W, without USB load; 11.3 W, with USB load

Connection data

Connection technology: communication/fieldbus	Web browser: 2 x RJ-45; 2 x USB 2.0 host (type A)
Connection technology: supply	1 x included 734-103 female connector featuring three CAGE CLAMP [®] connections

Physical data

Width	155 mm / 6.102 inch
Height	135 mm / 5.315 inch

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Depth	58 mm / 2.283 inch
Panel cutout (W x H)	(140 x 120) mm

Mechanical data

Weight	640 g
--------	-------

Environmental requirements

Surrounding air temperature (operation)	-20 ... 55 °C (when mounted vertically; -20 ... +50 °C, other mounting positions)
Surrounding air temperature (storage)	-20 ... 80 °C
Protection type	IP65
Note on protection type	IP65 (front side); IP20 (rear side), per EN 60529
Relative humidity (without condensation)	90 %
Mounting type	Clamping elements (included) or VESA mount (4 x M4x8)

Commercial data


PU (SPU)	1 Each
Packaging type	box
Country of origin	DE
GTIN	4055143839426
Customs tariff number	8471410000

Approvals / Certificates

Ship Approvals

Logo	Approval	Additional Approval Text	Certificate name
	DNV DNV Germany GmbH	DNVGL-CG-339,Dec.2019	TAA00001FS

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

Optional accessories

Memory card

Memory card



Item no.: 758-879/000-3102
Memory Card SD Micro; 2 GByte

www.wago.com/758-879/000-3102



Item no.: 758-879/000-3108
Memory Card SD Micro; pSLC-NAND; 8 GB; Temperature range: -40 to 90°C

www.wago.com/758-879/000-3108

Mounting

Mounting accessories



Item no.: 762-9001
e!DISPLAY7300T ; Clamping elements (4 pieces)

www.wago.com/762-9001

Software

Runtime software



Item no.: 2759-230/211-1000
e!RUNTIME; MicroBrowser; Single License; Online activation

www.wago.com/2759-230/211-1000

Downloads

Documentation

Manual

WAGO Touch Panel 600 Standard Line	1.5.0 2020. 12. 1.	pdf 2.5 MB	Download
---------------------------------------	-----------------------	---------------	----------

Bid Text

762-4101 docx - Datei	2018. 12. 21.	docx 21.1 kB	Download
--------------------------	---------------	-----------------	----------

762-4101 X81 - Datei	2019. 2. 19.	xml 5.5 kB	Download
-------------------------	--------------	---------------	----------

System Description

Touch Panel 600, system description		pdf 727.2 kB	Download
-------------------------------------	--	-----------------	----------

Additional Information

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



WAGO OPC UA Server	V 1.1.0 2021. 1. 28.	pdf 1.2 MB	Download
--------------------	-------------------------	---------------	----------

Runtime Software

Firmware

Firmware TP600	V 19.0 2021. 8. 19.	zip 165.4 MB	Download
----------------	------------------------	-----------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 762-4101		URL	Download
-----------------------	--	-----	----------

CAE data

ZUKEN Portal 762-4101		URL	Download
-----------------------	--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 762-4101 Touch Panel 600; 10.9 cm (4.3"); 480 x 272 pixels; 2 x USB, 2 x ETHERNET; Web Panel		URL	Download
--	--	-----	----------

Installation Notes

Product family

Standard Line

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.