

Preset counters electronic

2 presets, totalizer and batch counter

Display LED, 5-digits, programmable

NE216



NE216 - LED Preset counter

Features

- Preset counter with two presets
- Display 5-digits
- Totalizer, hour counter
- Operating mode, start count, scaling factor programmable
- Connection: Incremental encoder or digital sensors
- Step and trailing preset programmable
- Interface RS485

Technical data - electrical ratings

| | |
|----------------------------|--|
| Voltage supply | 22...50 VAC (50/60 Hz) 85...265 VAC (50/60 Hz) 12...30 VDC |
| Power consumption | 5 VA, 5 W |
| Sensor supply | AC: 24 VDC \pm 20 % / 100 mA DC: 9...28 VDC / 100 mA |
| Display | LED, 7-segment display |
| Number of digits | 5-digits |
| Digit height | 7.6 mm |
| Function | Preset counter Main counter with 2 presets Totalizer Hour counter |
| Scaling factor | 0.0001...9999.99 |
| Count modes | Adding or subtracting A-B (difference counting) A+B total (parallel counting) Up/Down A 90° B phase evaluation |
| Counting frequency | 3 Hz, 25 Hz, 10 kHz programmable |
| Operating modes | Step preset, Trailing preset, Time meter and hour counter |
| Data memory | >10 years in EEPROM |
| Reset | Button, electric or automatic |
| Outputs electronic | Optocoupler |
| Outputs relay | Normally open or closed, programmable |
| Output holding time | 0.01...99.99 s |
| Interface | RS485 |
| Standard DIN EN 61010-1 | Protection class II Overvoltage category II Pollution degree 2 |
| Emitted interference | DIN EN 61000-6-4 |
| Interference immunity | DIN EN 61000-6-2 |

Technical data - electrical ratings

| | |
|-------------------------|---|
| Programmable parameters | Operating modes Sensor logic Scaling factor Count mode Control inputs |
| Approvals | UL/cUL, CE conform |

Technical data - mechanical design

| | |
|-------------------------|--|
| Operating temperature | 0...+50 °C |
| Storing temperature | -20...+70 °C |
| Relative humidity | 80 % non-condensing |
| E-connection | Plug-in screw terminals |
| Core cross-section | 1.5 mm ² |
| Protection DIN EN 60529 | IP 65 face with seal |
| Operation / keypad | Membrane with softkeys |
| Housing type | Built-in housing |
| Dimensions W x H x L | 48 x 48 x 100 mm |
| Installation depth | 100 mm |
| Mounting | Clip frame |
| Cutout dimensions | 45 x 45 mm (+0.6) |
| Materials | Housing: Makrolon 6485 (PC) Keypad: Polyester |
| Weight approx. | 150 g |

