Main Product Characteristics:


V_{DSS}	20V
R_{DS}(on)	14mΩ (typ.)
I_D	8A①



TSSOP-8



Marking and pin Assignment



Schematic diagram

Features and Benefits:

- Advanced MOSFET process technology
- Ultra low on-resistance with low gate charge
- High Power and current handing capability
- 150℃ operating temperature
- G/S ESD protect 2KV (HBM)

Description:

The SSF2814EH2 series MOSFETs is a new technology, which combines an innovative technology and advance process. This new technology achieves low Rdson, energy saving, high reliability and uniformity, superior power density and space saving.

Absolute max Rating:

Symbol	Parameter	Max.	Units
I_D @ TC = 25°C	Continuous Drain Current	8 ①	A
I_D @ TC = 100°C	Continuous Drain Current	6.2 ①	
I_{DM}	Pulsed Drain Current ②	25	
P_D @TC = 25°C	Power Dissipation ③	2	W
	Linear Derating Factor	0.5	W/°C
V_{DS}	Drain-Source Voltage	20	V
V_{GS}	Gate-to-Source Voltage	± 10	V
T_J T_{STG}	Operating Junction and Storage Temperature Range	-55 to +150	°C


Thermal Resistance

Symbol	Characterizes	Typ.	Max.	Units
$R_{\theta JA}$	Junction-to-ambient (t ≤ 10s) ④	—	90	℃/W

Electrical Characterizes @T_A=25℃ unless otherwise specified


Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)DSS}$	Drain-to-Source breakdown voltage	20	—	—	V	V_{GS} = 0V, I_D = 250μA
$R_{DS(on)}$	Static Drain-to-Source on-resistance	—	14	20	mΩ	V_{GS}=4.5V,I_D = 7A
		—	18	—		T_J = 125°C
		—	20	28	mΩ	V_{GS}=2.5V,I_D = 5.5A
		—	24	—		T_J = 125°C
		—	38	50	mΩ	V_{GS}=1.8V,I_D = 5A
		—	42	—		T_J = 125°C
$V_{GS(th)}$	Gate threshold voltage	0.6	—	1	V	V_{DS} = V_{GS}, I_D = 250μA
I_{DSS}	Drain-to-Source leakage current	—	—	1	μA	V_{DS} = 20V,V_{GS} = 0V
		—	—	50		T_J = 125°C
I_{GSS}	Gate-to-Source forward leakage	—	—	100	nA	V_{GS} = 4.5V
		—	—	-100		V_{GS} = -4.5V
		—	—	10	uA	V_{GS} = 10V
		—	—	-10		V_{GS} = -10V
Q_g	Total gate charge	—	10	—	nC	I_D = 7A,
Q_{gs}	Gate-to-Source charge	—	2.3	—		V_{DS}=10V,
Q_{gd}	Gate-to-Drain("Miller") charge	—	3	—		V_{GS} = 4.5V
$t_{d(on)}$	Turn-on delay time	—	7.3	—	ns	V_{GS}=4.5V, V_{DS} =10V, R_{GEN}=3Ω,I_D =6.5
t_r	Rise time	—	60	—		
$t_{d(off)}$	Turn-Off delay time	—	18	—		
t_f	Fall time	—	5.9	—		
C_{iss}	Input capacitance	—	632	—	pF	V_{GS} = 0V
C_{oss}	Output capacitance	—	142	—		V_{DS} = 10V
C_{rss}	Reverse transfer capacitance	—	134	—		f = 1MHz

Source-Drain Ratings and Characteristics


Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	—	—	8 ①	A	MOSFET symbol showing the integral reverse p-n junction diode. 
I_{SM}	Pulsed Source Current (Body Diode)	—	—	25	A	
V_{sd}	Diode Forward Voltage	—	—	1.2	V	I_S=2.8A, V_{GS}=0V
t_{rr}	Reverse Recovery Time	—	35	—	nS	T_J = 25°C, I_F =7A, di/dt = 100A/μs
Q_{rr}	Reverse Recovery Charge	—	7.2	—	nC	

Test circuits and Waveforms


EAS Test Circuit:




Gate charge test circuit:



Switching Time Test Circuit:



Switching Waveforms:



Notes:

①Calculated continuous current based on maximum allowable junction temperature.

②Repetitive rating; pulse width limited by max. junction temperature.

③The power dissipation PD is based on max. junction temperature, using junction-to-case thermal resistance.

④The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with TA =25°C

Typical electrical and thermal characteristics




Figure 1: Typical Output Characteristics




Figure2. Typical Capacitance Vs. Drain-to-Source Voltage




Figure 3. Maximum Drain Current Vs. Case Temperature







Figure4. Maximum Effective Transient Thermal Impedance, Junction-to-Case

Mechanical Data：


TSSOP-8 Dimensions in Millimeters (UNIT:mm)







RECOMMENDED LAND PATTERN



Dimensions in millimeters

Symbols	Min.	Nom.	Max.
A	—	—	1.20
A1	0.05	—	0.15
A2	0.80	1.00	1.05
b	0.19	—	0.30
C	0.09	—	0.20
D	2.90	3.00	3.10
E	6.40 BSC		
E1	4.30	4.40	4.50
e	0.65 BSC		
L	0.45	0.60	0.75
θ	0°	—	8°

Dimensions in inches

Symbols	Min.	Nom.	Max.
A	—	—	0.047
A1	0.002	—	0.006
A2	0.031	0.039	0.041
b	0.007	—	0.012
C	0.004	—	0.008
D	0.114	0.118	0.122
E	0.252 BSC		
E1	0.169	0.173	0.177
e	0.026 BSC		
L	0.018	0.024	0.030
θ	0°	—	8°

NOTES：

1. All dimensions are in millimeters.
2. Dimensions are inclusive of plating
3. Package body sizes exclude mold flash and gate burrs. Mold flash at the non-lead sides should be less than 6 mils.
4. Dimension L is measured in gauge plane.
5. Controlling dimension is millimeter, converted inch dimensions are not necessarily exact.

Ordering and Marking Information

Device Marking: 2814EH2

Package (Available)

TSSOP-8

Operating Temperature Range

C : -55 to 150 °C

Devices per Unit

Package Type	Units/ Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Carton Box	Units/Carton Box
TSSOP-8	3000	2	6000	8	48000

Reliability Test Program

Test Item	Conditions	Duration	Sample Size
High Temperature Reverse Bias(HTRB)	T_j=125℃ to 150℃ @ 80% of Max V_{DSS}/V_{CES}/VR	168 hours 500 hours 1000 hours	3 lots x 77 devices
High Temperature Gate Bias(HTGB)	T_j=150℃@ 100% of Max V_{GSS}	168 hours 500 hours 1000 hours	3 lots x 77 devices

ATTENTION:

- Any and all Silikron products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Silikron representative nearest you before using any Silikron products described or contained herein in such applications.
- Silikron assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Silikron products described or contained herein.
- Specifications of any and all Silikron products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- Silikron Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all Silikron products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Silikron Semiconductor CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. Silikron believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the Silikron product that you intend to use.

Customer Service

Worldwide Sales and Service:

Sales@silikron.com

Technical Support:

Technical@silikron.com

Suzhou Silikron Semiconductor Corp.

11A, 428 Xinglong Street, Suzhou Industrial Park, P.R.China

TEL: (86-512) 62560688

FAX: (86-512) 65160705

E-mail: Sales@silikron.com