

Housing - VC-MEMV-T1-R-M20 - 1886595

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing with EMC coating and conductive seal, with metric cable entry, locking screws with knurled head, type 1

The illustration shows version VC-MEMV-T3-R-M25



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	231.8 GRM
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Height	65 mm
Width	33 mm
Length	59 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

General

Note	When using fiber optics, the bending radii of the cable manufacturers must be observed.
Type	VC1
Housing type	Sleeve housings
Color	nickel
Locking type	Screw locking, knurled head
Tightening torque, mounting screw	1.5 Nm \pm 0.3 Nm
No. of cable outlets	1

Housing - VC-MEMV-T1-R-M20 - 1886595

Technical data

General

Cable exit	Angled
Screw connection	none
Type of the screw connection	M20
Housing material	Zinc die-cast, surface bronzed and nickel-plated
Housing surface material	Nickel-plated
Seal material	EPDM, conductive
Material of locking screw	Nickel-plated brass

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27371205
eCl@ss 5.1	27371205
eCl@ss 6.0	27371205
eCl@ss 7.0	27371205
eCl@ss 8.0	27440202

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Approvals

GOST

Housing - VC-MEMV-T1-R-M20 - 1886595

Approvals

Ex Approvals

Approvals submitted

Approval details



Drawings

Dimensioned drawing

