

## Network cable - VS-OE-OE-94D-100,0 - 1416334


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Network cable, Ethernet CAT5 (1 Gbps), 8-position, PVC (reinforced) UV-resistant, deep black RAL 9005, shielded, free cable end, on free cable end, cable length: 100 m



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 474559
GTIN	4046356474559
Weight per Piece (excluding packing)	5,120.000 g
Custom tariff number	85444290
Country of origin	Germany

### Technical data

#### Dimensions

Length of cable	100 m
-----------------	-------

#### General data

Number of positions	8
Signal type/category	Ethernet CAT5, 1 Gbps
Transmission characteristics (category)	CAT5
Transmission speed	1 Gbps

#### Cable

Cable type	Ethernet
Cable type (abbreviation)	94D
UL AWM style	2464 (80°C/300 V)

## Network cable - VS-OE-OE-94D-100,0 - 1416334

### Technical data

#### Cable

Signal type/category	Ethernet CAT5 (IEC 11801), 1 Gbps
Cable structure	4x2xAWG26/7; SF/UTP
Conductor cross section	4x 2x 0.14 mm <sup>2</sup>
AWG signal line	26
Conductor structure signal line	7x 0.16 mm
Core diameter including insulation	0.98 mm ±0.05 mm
Wire colors	white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs	2 cores to the pair
Overall twist	4 pairs, twisted
Shielding	Aluminum-lined polyester foil, tinned copper braided shield
Optical shield covering	85 %
External sheath, color	black RAL 9005
Outer sheath thickness	0.8 mm
External cable diameter D	6.4 mm ±0.2 mm
Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	60 mm
Tensile strength GRP	80 N
Outer sheath, material	PVC (reinforced) UV-resistant
Material conductor insulation	PP
Conductor material	Bare Cu litz wires
Insulation resistance	≥ 5 GΩ*km
Conductor resistance	< 140 Ω/km
Cable capacity	< 56 nF/km
Wave impedance	100 Ω ±15 Ω (at 4 ... 100 MHz)
Signal speed	0.6 c
Nominal voltage, cable	72 V DC 300 V AC
Test voltage Core/Core	2500 V DC (2 s)
Test voltage Core/Shield	2500 V DC (2 s)
Flame resistance	According to VW-1
Resistance to oil	according to IEC 60811-2-1
Other resistance	UV resistant According to UL 1581, Section 1200
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (installation)	0 °C ... 50 °C
Shielded	yes

#### Environmental Product Compliance

# Network cable - VS-OE-OE-94D-100,0 - 1416334

## Technical data

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Cable cross section



Ethernet [94D]

## Classifications

eCl@ss

eCl@ss 10.0.1	27060390
eCl@ss 11.0	27061801

# Network cable - VS-OE-OE-94D-100,0 - 1416334

## Classifications

### eCl@ss

eCl@ss 4.0	24010400
eCl@ss 4.1	24010400
eCl@ss 5.0	19030300
eCl@ss 5.1	19030300
eCl@ss 6.0	27061800
eCl@ss 7.0	27061801
eCl@ss 9.0	27061801

### ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249

### UNSPSC

UNSPSC 6.01	26121616
UNSPSC 7.0901	26121616
UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121604
UNSPSC 18.0	26121604
UNSPSC 19.0	26121604
UNSPSC 20.0	26121604
UNSPSC 21.0	26121604

## Approvals

### Approvals

---

Approvals

EAC-RoHS

---

Ex Approvals

---

### Approval details

## Network cable - VS-OE-OE-94D-100,0 - 1416334

### Approvals

EAC-RoHS



RU D-  
DE.HB35.B.00385