

SPECIFICATION SHEET

JFW MODEL 50R-215

ROTARY ATTENUATOR

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-2200 MHz

Impedance 50 Ohms nominal

Attenuation Range 0-1 dB in 0.1 dB steps

VSWR 1.2:1 maximum DC-1000 MHz
1.4:1 maximum 1000-2200 MHz

Insertion Loss 1 dB maximum

Attenuation Accuracy ± 0.05 dB

RF Input Power 2 Watts average

Direction of Rotation Attenuation increases in a Clockwise direction

Indexing 30 degrees with stops at Minimum and maximum

RF Connector BNC, SMA or TNC female

Operating Temperature Range -20°C to +85°C

Lifetime 500,000 attenuation steps

Knob/Panel Mounting Drawing 092-8435-01

Outline Drawings 092-039 (50R-215 SMA)
092-427 (50R-215 BNC)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	04/19/1993			25776	09/29/2015	C	TRS 09/29/2015
9999	04/30/2003	A	TRS 05/16/2007	28157	10/05/2017	D	TRS 10/05/2017
20829	11/01/2011	B	TRS 11/01/2011				