

4831, solder terminal, screened, 3-pole, Audio Plug/Sockets, 2.5 mm




### Description

- Solder terminal :  
Screw-on mounting , from rear-side
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 3-pole , shielded , straight


### Technical Data

Diameter	2.5 mm	Allowable Operation Temp.	-20 °C to 70 °C
Number of Poles	3-pole	Terminal	solder terminal silver plated
Ratings DC	0.5 A / 30 VDC	Mounting	Screw-on mounting
Ratings AC	0.5 A / 30 VAC		wall thickness max. 2.1 mm
Dielectric Strength	500VDC	Housings	screened
Insulation Resistance	> 100 MΩ @ 500VDC	Style	straight
		Lifetime	5000 Insertions

### Dimensions



### Diagrams



## All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Sockets	2.5	3-pole	solder terminal	4831.2300

Most Popular.

Availability for all products can be searched real-time:<http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER>

**Packaging unit** 100 Pcs

## Mating Inlets/Plugs

### Category / Description

[Audio Plug/Sockets Overview complete](#)



4831, solder terminal, screened, 3-pole, Audio Plug/Sockets, 2.5 mm	4831.1300
4831, solder terminal, insulated, 3-pole, Audio Plug/Sockets, 2.5 mm	4831.1310
4831, solder terminal, insulated, 3-pole, Audio Plug/Sockets, 2.5 mm	4831.1320

[Audio Plug/Sockets further types to 4831.2300](#)