ACAD GENERATED DRAWING. DON'T CHANGE BY HAND.

REV	ECN NO.	APPD
A	HC-17-0082	ZO







规格 Specifications

额定负荷 Rating	DC 12V/50mA		
接触电阻Contact Resistance	500mΩ max.		
绝缘电阻Insulation resistance	DC100V 60S 100MΩ min.		
抗电强度Dielectric strength	AC250V(50~60HZ) 60S min.		
操作力Operation force	160±30gf	180±30gf	240±50gf
寿命试验Operating Life	300,000 cycles		
行程Travels	0.13±0.05mm		





CIRCUIT DIAGRAM
回路图



RECOMMENDED P.C.B. LAYOUT
安装尺寸图



LAND PATTERN PLAN
印刷电路板焊盘参考图

PRODUCT NO.: 1TS015A***-****-**** - **

- 轻触开关
- 3X2系列
- 外形:
  - A=两脚
  - B=四脚
- 按点颜色:
- 底座颜色:
- 贴膜颜色:
  - ⇩ 初始颜色则不启用
- 操作力度:
  - 160=160gf
  - 180=180gf
  - 200=200gf
  - 220=220gf
  - 240=240gf
- 手感:
  - 0=常规(弹片)
  - 1=大手感(弹片)
  - 2=小手感(弹片)
  - 3=特殊手感(弹片)
- 产品高度(H):
  - 050=0.5mm
  - 060=0.6mm
  - 070=0.7mm
- 材质:
  - 0=初始材质
  - 1=新增材质依次增加
- 其它:
  - CT=编带(非编带,不启用)

ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
5	KNOB	1	POLYAMIDE	BLACK
4	FILM	1	POLYAMIDE	WHITE
3	DOME	2	SUS301	Ag-PLATED
2	HOUSING	1	POLYAMIDE	BLACK
1	TERMINAL	1	PHOSPHOR BRONZE	Ag-PLATED

X. ± 0.2	X.° ± 0.2°	UNITS MM
.X ± 0.1	.X° ± 0.1°	MAT'L
.XX ± 0.01	.XX° ± 0.01°	FINISH
.XXX ± 0.002	.XXX° ± 0.005°	Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED. COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN PRECISION IND. CO., LTD.

NAME(INTENDED USE)
3X2 SERIES
TACT SWITCHES

PART NO.(INTENDED USE)
1TS015A***-****-***0

APPD: ZO 11/16'2017

CHKD: Li 11/16'2017

DR: WP.Lu 11/16'2017

HON YUAN
HON YUAN PRECISION IND. CO.,LTD.
SHENZHEN, CHINA, R.O.C.

TITLE: PRODUCT DRAWNG

DWG NO.: 1TS015A

SCALE	SHEET	REV.
25/1	1/1	A