


XMS500LV



<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	XMS
<b>Model</b>	XMS500
<b>Status</b>	Production
<b>Feature</b>	for Medical instruments 2MOPP
<b>Options</b>	With cover Class II input Top fan
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



**Electrical Characteristics**

Input	Single-phase
Input Voltage Range[AC]	90 to 264Vac
Input Voltage Range[DC]	
Efficiency	92% Typ.
Rated Output Voltage[DC]	36Vdc
Output Voltage Range[DC]	
Maximum Output Current	13.8A
Maximum Output Power	500W

**Package Type & Size**

Package / Mounting	Enclosed / Unit type
Width(W)	180mm Nom. (7.09in Nom.)
Height(H)	67.4mm Nom. (2.65in Nom.)
Depth(D)	107mm Nom. (4.21in Nom.)
Weight	

**Other**

Operating Temp. Range	0 to 50°C
Cooling	Forced air

Safety Standard(Certified)	IEC60601-1 CSA60601-1 EN60601-1 ES60601-1 UL60601-1 IEC60950-1 CSA60950-1 EN60950-1 UL60950-1
Safety Standard(Conformed)	IEC60065 CSA60065 EN60065 UL60065 IEC61010-1 EN61010-1
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.