


LOC	DIST	REVISIONS					
CM	00	P	LTR	DESCRIPTION	DATE	OWN	APVD
			W	REVISED PER ECO-12-007504	03AUG12	KH	SM

SUPERSEDED



- 2 CONTACTS ACCEPT 26 AWG WIRE WITH 1.52[.060] MAX INSULATION DIAMETER.
- 3 CONTACTS MUST ACCEPT 0.64±0.03[.025±.001] SQUARE POST AND REMAIN LOCKED IN POSITION.
- 4 IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY NOT APPEAR ON ALL ASSEMBLIES.
- 5 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 6 HOUSING FEATURES ARE: FEED THRU WITH LOCKING RAMP.
- 7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- 8 BLUE COLOR STRIPE ON HOUSING (NOT SHOWN) MAY BE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 08AUG2003 S. CARPENTER CHK 08AUG2003 D. BOSSI		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME MTA-100 CONNECTOR ASSEMBLY, 26 AWG, STANDARD	
		APVD 08AUG2003 D. BOSSI PRODUCT SPEC 108-1050			
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 0.13 [0.005] 4 PLC ± ANGLES ±		APPLICATION SPEC 114-1019			
MATERIAL 		FINISH 		SIZE A2	CAGE CODE 00779
				DRAWING NO C-640622	RESTRICTED TO —
CUSTOMER DRAWING				SCALE 5:1	SHEET 1 of 1
				REV W	