

Product data sheet

Characteristics

8502SDA2V06

NEMA Contactor, Type S, nonreversing, Size 2, 45A, 25 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 480VAC coil, NEMA 12

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 1,344.00 USD



Main

Product Type	Contacteur
Type	8502S
Control Circuit Type	Common control circuit
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Contacteur Type	Non-reversing
Current Rating	45 A
Number of Poles	3P
Phase	3 phase
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Maximum Voltage Rating	600 V AC
SCCR	Circuit-breaker 100 A maximum, SCCR: 100 kA at 480 V AC Fuse J 100 A maximum, SCCR: 100 kA at 600 V AC Fuse T 100 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 100 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 100 A maximum, SCCR: 100 kA at 600 V AC
Control Units	No control units
Pilot Light	No indicator
Auxiliary Contacts	Without
Control Circuit Fusing	Fuse not supplied
Electrical Connection	Screw clamp terminals
Enclosure Type	NEMA 12 painted sheet steel
Certifications	UL listed file E78351 CCN NLDX CSA

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Dec 11, 2020

NEMA Size	2
Height	15.98 in (406 mm)
Depth	9.29 in (236 mm)
Width	8.15 in (207 mm)

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901945642
Nbr. of units in pkg.	1
Package weight(Lbs)	19.31 lb(US) (8.76 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------