

19654 Eighth Street East P.O. Box 517 Sonoma, CA 95476 (707) 996.5201 www.worldproducts.com sales@worldproducts.com

WPANT30057-RA



Description / Application

This is a high gain Omni-directional antenna that operates in the 5.8 GHz Wi-Fi / WLAN band. It comes with a Type-N female connector. The antenna is at DC ground to ensure protection against lightning.

We can assist your engineers to optimize mounting positions for these antennas in your specific application and can further customize the antennas for your specific needs. Please contact sales@worldproducts.com with your specific application requirements.

Electrical Properties	
Operating Frequency	5.725 – 5.850 GHz
Approximate Antenna Impedance [Ω]	50 Ω
VSWR – Typical	< 2:1
Peak Gain [dBi] (Typical)	10 dBi
Polarization	Vertical
Pattern	Omni-Directional
Accepted Power [W] (Max)	5 Watts
Lightning Protection	DC ground

Mechanical / Environmental Properties	
Antenna Dimensions	23.6" X 2.3" (600mm X 58mm)
Antenna Color	White
Connector	Type-N Female
Antenna Radome	Fiberglass
Operating / Storage Temperature	-40°C to +90°C
Environmental	Meets standards for UL 94V-0
Hazardous Materials	RoHS Compliant

Rev: 2.0 Created on: June 20, 2013 Created by: MKS Approved by: BP Page | 1





Rev: 2.0 Created on: June 20, 2013 Created by: MKS Approved by: BP Page | 2