DIELECTRIC LABORATORIES
a Knowles Precision Devices brand

PRECISION DEVICES knowles
COMPEX • DLI • JOHANSON MFG
NOVACAP • SYFER • VOLTRONICS
www.knowlescapacitors.com

5.70 GHz Surface Mount Bandpass Filter

B058MD7S

DESCRIPTION

One of DLI's surface mountable catalog bandpass filters designed for the 5G band. This filter utilizes DLI's low loss temperature stable materials which offer small size and minimal performance variation over temperature. The catalog BPF's are offered in a variety of frequency bands, which offers a drop in solution with highly repeatable performance.

FEATURES


- Small Size
- Fully Shielded Component
- Solder Surface Mount Package
- Moisture Sensitivity Level: MSL1
- Frequency Stable over Temperature
- Operating & Storage Temp: -55˚C to +125˚C
- Characteristic Impedance: 50Ω

SPECIFICATIONS*

Parameter	Frequency Range (GHz)	Min	Typ.	Max
Insertion Loss (dB)	5.5 - 6.1		2.3	2.8
Return Loss (dB)		10	12	18
Low Side Rejection (dB)	DC - 4.65		40	
High Side Rejection (dB)	7.0 to 16.0		40	
Input Power (W)				TBD
Size (L x W x H)	0.475 x 0.275 x 0.103 in 12.07 x 6.99 x 2.62 mm			

*Electrical specifications based on typical probed performance at room temperature. Insertion loss shall vary ±0.5dB over temperature.

Typical Measured Performance



2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710 | KCCSales@knowles.com

March 2018


DIELECTRIC LABORATORIES
a Knowles Precision Devices brand

5.70 GHz Surface Mount Bandpass Filter


B058MD7S

knowles PRECISION DEVICES
COMPEX • DLI • JOHANSON MFG
NOVACAP • SYFER • VOLTRONICS
www.knowlescapacitors.com

Physical Dimensions



Recommended PCB Layout



- 50Ω trace dimensions are application specific.
- Ensure adequate grounding beneath the part.

ISO 9001 QMI-SAI Global
AS 9100 QMI-SAI Global
RoHS 2011/65/EU Lead Free

2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710 | KCCSales@knowles.com

March 2018