

IPC-610-F

Classic 4U 15-Slot Rackmount Chassis




Features

- 4U rackmount chassis supports up to 15 cards
- Shock-resistant disk drive bay design holds up to three 5.25" and two 3.5" (one front-accessible & one internal) disk drives
- Special hold-down clamp design with rubber cushions protects the cards from shock and vibration
- Power and HDD activity notification improves system availability
- Front-accessible air filter for easy system maintenance
- Lockable front door prevents unauthorized access
- 300W / 400W AC and 300W DC ATX power supply options




Specifications

| | | | | | |
|---------------------|--------------------------|------------------------|--|--|----------------------------------|
| Drive Bay | 3.5" | External | 1 | Internal | 1 |
| | 5.25" | | 3 | | - |
| Cooling | Fan | | 1 (12 cm / 85 CFM) | | |
| | Air Filter | | Yes | | |
| Front I/O Interface | USB | | 2 | | |
| | PS/2 | | 1 | | |
| Miscellaneous | LED Indicators | | Power, HDD, keyboard lock | | |
| | Control | | Power, system reset and keyboard lock switches | | |
| | Rear Panel | | Backplane version: One 9-pin D-Sub opening Motherboard version: Five 9-pin D-Sub & one 68-pin SCSI openings | | |
| Environment | Temperature | Operating | 0 ~ 40° C (32 ~ 104° F) | Non-Operating | -20 ~ 60° C (-4 ~ 140° F) |
| | Humidity | | 10 ~ 85% @ 40° C, non-condensing | | 10 ~ 95% @ 40° C, non-condensing |
| | Vibration (5 ~ 500 Hz) | | 1 Grms | | 2 G |
| | Shock | | 10 G (with 11 ms duration, half sine wave) | | 30 G |
| | Physical Characteristics | Dimensions (W x H x D) | | IPC-610BP: 482 x 177 x 449 mm (19" x 7" x 17.8") IPC-610MB: 482 x 177 x 499 mm (19" x 7" x 19.6") | |
| | Weight | | 16.2 kg (35.6 lb) | | |



Dimensions

Unit: mm [inch]



Ordering Information

| Part Number | Power Supply |
|----------------------------|---------------------------------------|
| Backplane Version | |
| IPC-610BP-00FEE | Without power supply, with ATX switch |
| IPC-610BP-30FEE | PS8-300ATX-ZBE |
| Motherboard Version | |
| IPC-610MB-00FEE | Without power supply, with ATX switch |
| IPC-610MB-30FEE | PS8-300ATX-ZBE |

Optional Accessories

| Part Number | Description |
|--------------|---|
| IPC-DT-3120E | Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays |
| IPC-DT-5230E | Mobile rack for converting dual 5.25" drive bays to three 3.5" SAS/SATA HDD trays |

Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

| Part Number | 80 Plus Grade | Wattage | Type | Input |
|-----------------|---------------|---------|---------------|---------------------------|
| PS8-300ATX-ZBE | Bronze | 300W | Single | AC 100 ~ 240 (full range) |
| PS8-400ATX-ZE | Bronze | 400W | Single | AC 100 ~ 240 (full range) |
| PS-300ATX-DC48E | - | 300W | Single | DC - 48V |
| RPS8-350ATX-XE | Gold | 350W | 1+1 Redundant | AC 100 ~ 240 (full range) |
| RPS8-500ATX-XE | Bronze | 500W | 1+1 Redundant | AC 100 ~ 240 (full range) |

Spare Parts

| Part Number | Description |
|----------------|------------------------------|
| 2130006190S000 | Fan filter 120 x 100 x 15 mm |