Product data sheet
Characteristics

HRL36050M38X
Motor circuit protector, PowerPact H, 50A, 3 pole, 600V, 100kA

Price** : 2,410.00 USD



Main

Product or component type	Motor Circuit Protector
Range of product	PowerPact H
Trip Unit Type	Electronic, standard,
Breaking capacity code	R

Complementary

Line Rated Current	50 A
Number of Poles	3P
Interrupt Rating	200 kA 240 V AC 200 kA 480 V AC 100 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Magnetic hold current	500 A
Magnetic tripping current	1300 A
Maximum Height	6.4 in (162.56 mm)
Width	4.12 in (104.65 mm)
Depth	4.36 in (110.74 mm)

Environment

Product certifications	CSA CCC CE UL Listed

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	IEC
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01108-H/J HIGH INTERUPT UNIT MT CB/SW
Discount Schedule	DE2
Package weight(Lbs)	5.00 lb(US) (2.268 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information