



MATERIAL & FINISHES
 INSULATOR - PBT GLASS FILLED UL94V-0
 CONTACT- BRASS
 SHELL - STEEL
 PLATING - CONTACT
 - CONTACT
 1. GOLD FLASH (COMPLETE)
 2. SELECTIVE GOLD OVER NICKEL PLATED (CONTACT AREA) —
 TIN OVER NICKEL PLATED (TAIL AREA)
 - SHELL
 Tin OR Nickel OVER COPPER PLATED

ELECTRICAL CHARACTERISTICS
 RATING CURRENT : 3A
 CONTACT RESISTANCE : <20mΩ
 INSULATION RESISTANCE : >1000MΩ at 500V
 DIELECTRIC VOLTAGE : 1000V /MIN
 OPERATING TEMPERATURE : -50° C TO+105° C

POLES	PART No.	Dim. A	Dim. B	Dim. C	Dim. D
9	DMS-9S	16.33	24.99	30.81	19.25
15	DMS-15S	24.66	33.32	39.14	27.51
25	DMS-25S	38.38	47.04	53.04	41.20
37	DMS-37S	54.84	63.50	69.40	57.5

TOLERANCE TABLE

.0	±0.30
.00	±0.15
.000	±0.05

APPROVED: DATE:

CHECKED: DATE:

DRAWN: DATE:

LYF 2010-11-02

深圳市灿科盟实业有限公司
 Ckmtw CHANKLEMENT INDUSTRYCO., LTD

TITLE: DMS-XP 母头 光孔

P/N	/
UNIT	mm
SCALE	free
FILE NO.	Ckmtw-DMS-0002
REV.	A