

RTW05-30R



Sales Region	Worldwide
Series	RTW
Status	Production
Feature	
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	
Efficiency	86% Typ.
Rated Output Voltage[DC]	5V
Output Voltage Range[DC]	4 to 5.8V
Maximum Output Current	30A
Maximum Output Power	150W

Cases Shape & Size

Case'□ shape	Unit
Width(W)	30mm Nom.
Height(H)	92mm Nom.
Depth(D)	180mm Nom.
Weight	520g Typ.

Other

Operating Temp. Range	-10 to 71°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 (C-UL) EN60950-1 (TUV)
Safety Standard(Conformed)	Den-an Appendix 8 at 100VAC only
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.