

Part Number: E1000S

Revision Level: 702

Date: 10/29/2007

2C 22 SOLID BC SR-PVC PVC
Sound, Alarm & Security Cable
A. CONSTRUCTION
DIAMETERS

Conductor:	#22 AWG Solid Bare Copper	0.025" nom.
Insulation:	0.007" Wall Semi-Rigid Polyvinyl Chloride	0.039" nom.
Cable:	2C @ 4.00" LHL	0.088" nom.
Jacket:	0.015" Wall Polyvinyl Chloride – Gray	0.118" +/- 0.006"
Print Legend:	CAROL A (R) 22 AWG - - E1000S - - 75C E60233-8 (UL) CL3R --- C(UL) CMR - - MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000' TO 0')	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3R
National Electrical Code	Article 800
UL Standard 444	Type CMR

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	300V
CONDUCTOR D.C. RESISTANCE:	16.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	28.57 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	67.3 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red