v KODENSHI AUK

SBT2222AU

NPN Silicon Transistor


Descriptions

- General purpose application
- Switching application

Features

- Low Leakage current
- Low collector saturation voltage enabling low voltage operation
- Complementary pair with SBT2907AU

PIN Connection



SOT-323

Ordering Information

Type NO.	Marking	Package Code
SBT2222AU	IQ □ ① ②	SOT-323

①Device Code ② Year&Week Code

Absolute maximum ratings

Ta=25°C

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	V_{CBO}	75	V
Collector-Emitter voltage	V_{CEO}	40	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	600	mA
Collector dissipation	P_C^*	350	mW
Junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-55~150	°C

* : Package mounted on 99.5% alumina 10×8×0.6mm

Electrical Characteristics

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	BV_{CBO}	I_C=10μA, I_E=0	75	-	-	V
Collector-Emitter breakdown voltage	BV_{CEO}	I_C=1mA, I_B=0	40	-	-	V
Emitter-Base breakdown voltage	BV_{EBO}	I_E=10μA, I_C=0	5	-	-	V
Collector cut-off current	I_{CBO}	V_{CB}=75V, I_E=0	-	-	20	nA
DC current gain	h_{FE}	V_{CE}=10V, I_C=10mA	100	-	-	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	I_C=150mA, I_B=15mA	-	-	0.4	V
Transition frequency	f_T	V_{CE}=20V, I_C=20mA, f=100MHz	250	-	-	MHz
Collector output capacitance	C_{ob}	V_{CB}=10V, I_E=0, f=1MHz	-	-	8	pF
Delay time	t_d	V_{CC}=30V_{dc}, $V_{BE(off)}$=0.5V_{dc}, I_C=150mA_{dc}, I_{B1}=15mA_{dc}	-	-	10	ns
Rise time	t_r		-	-	25	ns
Storage time	t_s	V_{CC}=30V_{dc}, I_C=150mA_{dc}, I_{B1}=I_{B2}=15mA_{dc}	-	-	225	ns
Fall Time	t_f		-	-	60	ns

Electrical Characteristic Curves

Fig. 1 P_C-T_a




Fig. 2 h_{FE}-I_C




Fig. 3 $V_{CE(sat)}$-I_C








Fig. 4 C_{ob}-V_{CB}





Outline Dimension












SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	0.90	-	1.25	
A1	0.00	-	0.10	
A2	0.85	0.90	0.95	
b	0.30	-	0.40	
c	0.10	-	0.25	
D	1.90	2.00	2.10	
E	1.95	2.10	2.25	
E1	1.15	1.25	1.35	
e	0.65BSC			
e1	1.20	-	1.40	
L	0.10	-	-	
L1	0.12BSC			

※Recommend PCB solder land [Unit: mm]



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.