



Unit: Inch / mm

POSITIONS	Socket Dimensions				
	A	B	C	D	E
15	.643 (16.33)	.984 (24.99)	1.213 (30.81)	.759 (19.28)	.277 (7.04)
26	.971 (24.66)	1.312 (33.32)	1.541 (39.14)	1.083 (27.51)	.271 (6.88)
44	1.511 (38.38)	1.852 (47.04)	2.008 (50.94)	1.626 (41.30)	.271 (6.88)
62	2.159 (54.84)	2.500 (63.50)	2.729 (69.32)	2.272 (57.71)	.275 (7.00)

SPECIFICATIONS:
Material:
 Insulator: PBT, glass reinforced, rated UL 94V-0
 Insulator color: Black
 Contacts: Phosphor Bronze
 Plating:
 Gold Flash over Nickel underplate overall
Electrical:
 Operating voltage: 250 VAC max
 Current rating: 5 Amps max
 Insulation resistance: 5000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 1000 VAC for 1 minute
Temperature Rating:
 Operating temperature: -65°C to +125°C

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED
 INCHES: .X ± .10 Ø.X ± .015
 .XX ± .020 Ø.XXX ± .010
 .XXX ± .015

ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

D-SUB, HIGH DENSITY, STRAIGHT FEMALE PCB

TITLE: _____
 SIZE: _____
 PART NO.: _____
 HDTXX-ST-SL

A

DRAWN: SS
 CHECKED: _____
 APPROVED: _____

DATE: 11/15/04
 SCALE: NTS
 SHEET 1 OF 1