


技术参数 SPECIFICATIONS

- 适用线规 (Applicable wires) : AWG24#~16#
- 温度范围 (Temperature range) : -25℃~85℃
- 额定电压 (Voltage rating) : 300V.Ac/Dc
- 额定电流 (Current rating) : 15A max
- 接触电阻 (Contact resistance) : ≤0.01Ω
- 绝缘电阻 (Insulation resistance) : ≥1000MΩ
- 耐压 (Withstand voltage) : 2000V.Ac/1min
- 材料 (Material) :
 - 壳体 (Housing) : 尼龙 (PA66) UL94V-2 (0)
 - 端子 (Terminal) : 黄铜 (Brass Tin/plated)
 - 磷青铜 (phos.bronze Tin/plated)

.187" /250# 端子 TERMINAL


| 型号 Type | 适用线规 Applicable wires | 尺寸 Dimensions (mm) | | | | 示意图 Sample | 数量 Quantity | | | |
|------------|--------------------------|--------------------|----------------|--------------------|-----|---------------|----------------|------|---|-------------------|
| | | mm ² | AWG# | 材料 Material | W | | | L | E | 材料厚度 Thickness |
| HX480N-01T | STO-01T-187N | 0.2~0.5 | 24~20 | | 5.7 | 15.0 | 6.5 | 0.35 | | 10000PCS/卷 |
| HX480N-41T | STO-41T-187N | 0.5~1.25 | 20~16 | 黄铜 Brass | 5.7 | 15.0 | 6.5 | 0.35 | A | 10000PCS/卷 |
| HX480N-61T | STO-61T-187N | | (UL1015) 20+18 | | 5.7 | 15.0 | 6.5 | 0.35 | | 10000PCS/卷 |
| HX4.8Z-21T | 730494-3 | 0.5~1.25 | 20~16 | 磷青铜 Phos.bronze | 5.6 | 18.0 | 6.0 | 0.3 | B | 2500PCS/盒 |




| 型号 Type | 尺寸 Dimensions (mm) | | | | |
|------------|--------------------|-----|-----|------|-----|
| | A | B | C | D | F |
| .187" | 7.0 | 3.6 | 4.8 | φ1.5 | 0.5 |

HX480N-1T


(A)



HX4.8Z-2A (610455-2P/35941-0200)




HX4.8Z-3A (611191)



HX4.8Z-21T

(B)



HX4.8XZ-3P (610439-3P)

