THINKI SEMICONDUCTOR ®

Pb Free Plating Product

MURB1020CTR/MURB1030CTR/MURB1040CTR/MURB1060CTR RoHS

10.0 Ampere Surface Mount Dual Common Anode Ultra Fast Recovery Rectifiers

Features

- ★ Latest GPP EPI P/G Technology
- ★ Good Soft Recovery Characteristics
- ★ Ideally Suited for Automatic Assembly
- ★ Low Forward Voltage
- ★ High Surge Current Capability
- ★ Low Leakage Current

Applications

- ★ Freewheeling, Snubber, Clamp
- ★ Inversion Welder
- ★ PFC
- ★ Plating Power Supply
- ★ Ultrasonic Cleaner and Welder
- ★ Converter & Chopper
- ★ UPS/LED SMPS/HID

D2PAK/TO-263 Unit : inch (mm)





Positive Common Cathode Suffix "CT" | Negative Common Anode Suffix "CTR" | Doubler Tandem Polarity Suffix "CTD" | Series Tandem Polarity Suffix "CTS"

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	MURB1020CTR	MURB1030CTR	MURB1040CTR	MURB1060CTR	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	200	300	400	600	V
RMS Reverse Voltage	$V_{R(RMS)}$	140	210	280	420	V
Average Rectified Output Current Total Device @T_C = 100°C Per Diode	I_O	10.0 5.0				A
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	100				A
Forward Voltage per diode @I_F = 5.0A	V_{FM}	0.98	1.3		1.7	V
Peak Reverse Current @T_C = 25°C At Rated DC Blocking Voltage @T_C = 100°C	I_{RM}	5.0 100				μA
Reverse Recovery Time (Note 1)	t_{rr}	35	50			nS
Typical Junction Capacitance (Note 2)	C_J	70	50			pF
Thermal Resistance Junction to Ambient (Note 3) Thermal Resistance Junction to Lead (Note 3)	$R_{\theta JA}$ $R_{\theta JC}$	30 1.5				°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150				°C

Note: 1. Measured with I_F = 0.5A, I_R = 1.0A, I_{RR} = 0.25A.
2. Measured at 1.0 MHz and applied reverse voltage of 4.0 V DC.
3. Mounted on PCB with minimum recommended pad sizes per diode.

© 1995 Thinki Semiconductor Co., Ltd.

Download from alldatasheet.com

RATINGS AND CHARACTERISTICS CURVES

(T_A=25°C unless otherwise noted)



Fig. 1 Forward Current Derating Curve



Fig. 2 Typical Forward Characteristics



Fig. 3 Forward Surge Current Derating Curve



Fig. 4 Typical Reverse Characteristics



Fig. 5 Forward Power Dissipation



Fig. 6 Typical Junction Capacitance

© 1995 Thinki Semiconductor Co., Ltd.

Download from alldatasheet.com