


isc Thyristors
BTA312X-600D
DESCRIPTION

- With TO-220F packaging
- High operating junction temperature
- Very high commutation performance maximized at each gate sensitivity
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- High temperature, high power motor control
- Solid state relays; heating and cooking appliances
- Switching applications


ABSOLUTE MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	UNIT
V_{DRM}	Repetitive peak off-state voltage	600	V
V_{RRM}	Repetitive peak reverse voltage	600	V
$I_{\text{T(AV)}}$	Average on-state current	12	A
I_{TSM}	Surge non-repetitive on-state current	95 105	A
$P_{\text{G(AV)}}$	Average gate power dissipation (over any 20 ms period)	0.5	W
T_j	Operating junction temperature	-40~150	$^\circ\text{C}$
T_{stg}	Storage temperature	-40~150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
I_{RRM}	Repetitive peak reverse current	$V_R=V_{\text{RRM}}$ Rated; $V_D=V_{\text{DRM}}$ Rated; $T_j=125^\circ\text{C}$		0.5	mA
I_{DRM}	Repetitive peak off-state current				
V_{TM}	On-state voltage	$I_T=15\text{A}$		1.6	V
I_{GT}	Gate-trigger current	$V_D=12\text{V}; I_T=0.1\text{A};$	I	5	mA
			II	5	
			III	5	
V_{GT}	Gate-trigger voltage	$V_D=12\text{V}; I_T=0.1\text{A};$		1.5	V