

Product Information

MX6008LN-4SFP Series

Compliant with EN50155, EN50121-3-2,
EN55011, IEC61373

**4+4G-port Din-Rial Layer 3 Gigabit Managed
Ethernet switches**



Features

- ❖ 4 10/100BaseT(X) ports (DB9 Ports)
- ❖ 4 1000BaseSFP slots
- ❖ Layer-3 Switching, Supports Static Routing, RIP V1/V2, OSPF
- ❖ RingOn (recovery time < 15ms), RSTP for Network Redundancy
- ❖ Fanless, -40 to +85°C operating temperature range
- ❖ 12~36VDC or 10~24VAC power supply range

HENRICHTM
Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

MX6008LN-4SFP series switches, which boast compact design, highly integration and reliability, are gigabit managed industrial Ethernet switches. The switches are equipped with not only L2 functions but also L3 routing. They are capable of providing power information transmission and network management in harsh industrial environments. They support up to 4 10/100Mbps DB9 ports and 4 Gigabit SFP Slots. They support redundant power supply input, ranging from 10~24VAC or 12~36VDC. As for installation, they can be installed with Din-rail.

Specifications

Technology		Switch Properties	
Standard :	IEEE802.3, 802.3u, 802.3z, 802.3ab,	L3 Host table :	4K
Processing Type :	Store and forward	MAC Table Size :	16K
Broadcast Storm :	Automatic Broadcast Storm Control	Priority Queues :	4
Management :	by Web Browser	Max. Number VLANs :	64
RingOn :	Recovery Time within 15ms	VLAN ID Range :	VID 1 to 4094
Flow Control :	IEEE802.3x Flow Control, Back Pressure Flow Control	IGMP Groups :	256
Protocols :	IGMP Snooping, GMRP, SNMPv1/v2c/v3, DHCP Client, HTTP, HTTPS, Telnet, NTP Client	Interface	
	<p>L3 Functions</p> <ul style="list-style-type: none"> • Static IP routing • OSPFv1/v2 • RIPv1/v2 • VRRP • IGMP v2/v3 Multicast Listener Protocol • Firewall, NAT and port mapping • File sharing based on the SAMBA service • FTP service based on STUPID-FTP • SSH secure access service based on OPENSSH • Add access, control WEB <p>L2 Functions</p> <ul style="list-style-type: none"> • IEEE 802.1Q Static VLAN and VLAN Label • Link Layer Management Protocol (LLDP) • IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) • IGMP SNOOPING • RingOn™ Redundant Technology, recovery time <15ms • RingOpen Redundancy <p>Management Tools</p> <ul style="list-style-type: none"> • Web Interface (HTTP and HTTPS) • Console port and Command Line Interface(CLI) controlled by SSHv2 • SNMPv1/v2c/v3 • Flexible configuration and log file management • Managing local file through HTTP, FTP, TFTP and SCP • Syslog(System log file and remote syslog server) • SNTP(NTP Client) • Software Online Upgrading 	RJ45 Port :	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
		Fiber Module :	1000Base-LX (4 SFP slots)
		LED Indicators :	Power, Port Status
		Console port :	RJ45 Port
		Output Warning :	Relay, Standard 2 Pin
		Power Requirements	
		Input Voltage :	12~36VDC @ 24W MAX 10~24VAC @ 24VA MAX
		Input Connection :	Grid panel terminal blocks Standard 4 pin input connection (optional)
		Physical Characteristics	
		Case :	Slim Metal Case, IP30 Design
		Dimensions :	55.2×180×148mm
		Installation :	DIN Rail or Panel Mounting
		Environment Limits	
		Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 85°C
		Storage Temp. :	-40 to 85°C
		Ambient Relative Humidity :	5 to 95%(Non-condensing)
		Standards and Certifications	
		EMI :	FCC Part15, CISPR(EN55022) Class A
		EMS :	EN61000-4-2(ESD) Level 4, EN61000-4-3(RS) Level 4, EN61000-4-4(EFT) Level 4, EN61000-4-5(Surge) Level 4, EN61000-4-6(CS) Level 4, EN61000-6-2
		Rail Traffic :	EN50155, EN50121-3-2, EN55011, IEC61373
		Shock :	IEC 60068-2-27
		Freefall :	IEC 60068-2-32
		Vibration :	IEC 60068-2-6
		Warranty	
		Warranty Period :	3 years

Ordering Information

MX6008LN-4SFP Series

MX6008LN-4SFP-4DB9	Layer 3 Din-rail Managed, 4 x 100Mbps Copper Port, DB9 Interface, 4 x Gigabit SFP Fiber Port, Industrial Temperature -10°C to +60°C, Power Input 12~36VDC or 10~24VAC
MX6008LN-4SFP-4DB9-W	Layer 3 Din-rail Managed, 4 x 100Mbps Copper Port, DB9 Interface, 4 x Gigabit SFP Fiber Port, Industrial Wide Temperature -40°C to +85°C, Power Input 12~36VDC or 10~24VAC