

## 4 BIT SYNCHRONOUS UP/DOWN COUNTERS

- **HIGH SPEED**  
 $f_{MAX} = 48 \text{ MHz (TYP.) AT } V_{CC} = 5 \text{ V}$
- **LOW POWER DISSIPATION**  
 $I_{CC} = 4 \mu\text{A (MAX.) AT } T_A = 25^\circ\text{C}$
- **HIGH NOISE IMMUNITY**  
 $V_{NIH} = V_{NIL} = 28 \% V_{CC} \text{ (MIN.)}$
- **OUTPUT DRIVE CAPABILITY**  
 $10 \text{ LSTTL LOADS}$
- **SYMMETRICAL OUTPUT IMPEDANCE**  
 $|I_{OH}| = I_{OL} = 4 \text{ mA (MIN.)}$
- **BALANCED PROPAGATION DELAYS**  
 $t_{PLH} = t_{PHL}$
- **WIDE OPERATING VOLTAGE RANGE**  
 $V_{CC} \text{ (OPR)} = 2 \text{ V TO } 6 \text{ V}$
- **PIN AND FUNCTION COMPATIBLE**  
 WITH 54/74LS190/191

### DESCRIPTION



The M54/74HC190/191 are high speed CMOS 4-BIT SYNCHRONOUS UP/DOWN COUNTERS fabricated in silicon gate C<sup>2</sup>MOS technology.

They have the same high speed performance of LSTTL combined with true CMOS low power consumption.


State changes of the counter are synchronous with the LOW-to-HIGH transition of the Clock Pulse input.

An asynchronous parallel load input overrides counting and loads the data present on the DATA inputs into the flip-flops, which makes it possible to use the circuits as programmable counters. A countenable input serves as the carry/borrow input in multi-stage counters. Control input, Down/Up, determines whether a circuit counts up or down. A MAX/MIN output and a Ripple Clock output provide overflow/underflow indication and make possible a variety of methods for generating carry/borrow signals in multi-stage counter applications.

All inputs are equipped with protection circuits against static discharge and transient excess voltage.




## INPUT AND OUTPUT EQUIVALENT CIRCUIT




## PIN DESCRIPTION

| PIN No       | SYMBOL                     | NAME AND FUNCTION                         |
|--------------|----------------------------|-------------------------------------------|
| 3, 2, 6, 7   | QA to QD                   | Flip-Flop Outputs                         |
| 4            | $\overline{\text{ENABLE}}$ | Count Enable Input (Active LOW)           |
| 5            | $\overline{\text{U/D}}$    | Parallel Data Input                       |
| 11           | LOAD                       | Load Input (Active LOW)                   |
| 12           | MA/MI OUT                  | Terminal Count Output                     |
| 13           | $\overline{\text{RC}}$     | Ripple Clock Output (Active LOW)          |
| 14           | CLOCK                      | Clock Input (LOW to HIGH, Edge-triggered) |
| 15, 1, 10, 9 | DA to DD                   | Data Inputs                               |
| 8            | GND                        | Ground (0V)                               |
| 16           | Vcc                        | Positive Supply Voltage                   |

## IEC LOGIC SYMBOL (HC190)



## IEC LOGIC SYMBOL (HC191)




## TRUTH TABLE

| INPUTS |        |     |           | OUTPUTS    |    |    |    | FUNCTION    |
|--------|--------|-----|-----------|------------|----|----|----|-------------|
| LOAD   | ENABLE | D/U | CLOCK     | QA         | QB | QC | QD |             |
| L      | X      | X   | X         | a          | b  | c  | d  | PRESET DATA |
| H      | L      | L   | $\square$ | UP COUNT   |    |    |    | UP COUNT    |
| H      | L      | H   | $\square$ | DOWN COUNT |    |    |    | DOWN COUNT  |
| H      | H      | X   | $\square$ | NO CHANGE  |    |    |    | NO COUNT    |
| H      | X      | X   | $\square$ | NO CHANGE  |    |    |    | NO COUNT    |


X: Don't Care

a - d: The level of steady state inputs at inputs a through d respectively






TIMING CHART (HC190)



TIMING CHART (HC191)



**ABSOLUTE MAXIMUM RATINGS**

| Symbol                              | Parameter                                    | Value                         | Unit |
|-------------------------------------|----------------------------------------------|-------------------------------|------|
| V <sub>CC</sub>                     | Supply Voltage                               | -0.5 to +7                    | V    |
| V <sub>I</sub>                      | DC Input Voltage                             | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| V <sub>O</sub>                      | DC Output Voltage                            | -0.5 to V <sub>CC</sub> + 0.5 | V    |
| I <sub>IK</sub>                     | DC Input Diode Current                       | ± 20                          | mA   |
| I <sub>OK</sub>                     | DC Output Diode Current                      | ± 20                          | mA   |
| I <sub>O</sub>                      | DC Output Source Sink Current Per Output Pin | ± 25                          | mA   |
| I <sub>CC</sub> or I <sub>GND</sub> | DC V <sub>CC</sub> or Ground Current         | ± 50                          | mA   |
| P <sub>D</sub>                      | Power Dissipation                            | 500 (*)                       | mW   |
| T <sub>stg</sub>                    | Storage Temperature                          | -65 to +150                   | °C   |
| T <sub>L</sub>                      | Lead Temperature (10 sec)                    | 300                           | °C   |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these condition is not implied.

(\*) 500 mW: ≡ 65 °C derate to 300 mW by 10mW/°C: 65 °C to 85 °C

**RECOMMENDED OPERATING CONDITIONS**

| Symbol                          | Parameter                                                         |                         | Value                     | Unit     |
|---------------------------------|-------------------------------------------------------------------|-------------------------|---------------------------|----------|
| V <sub>CC</sub>                 | Supply Voltage                                                    |                         | 2 to 6                    | V        |
| V <sub>I</sub>                  | Input Voltage                                                     |                         | 0 to V <sub>CC</sub>      | V        |
| V <sub>O</sub>                  | Output Voltage                                                    |                         | 0 to V <sub>CC</sub>      | V        |
| T <sub>op</sub>                 | Operating Temperature: <b>M54HC Series</b><br><b>M74HC Series</b> |                         | -55 to +125<br>-40 to +85 | °C<br>°C |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time                                          | V <sub>CC</sub> = 2 V   | 0 to 1000                 | ns       |
|                                 |                                                                   | V <sub>CC</sub> = 4.5 V | 0 to 500                  |          |
|                                 |                                                                   | V <sub>CC</sub> = 6 V   | 0 to 400                  |          |

## DC SPECIFICATIONS

| Symbol          | Parameter                 | Test Conditions        |                                                              | Value                                   |      |      |                      |      |                       |      |      | Unit |
|-----------------|---------------------------|------------------------|--------------------------------------------------------------|-----------------------------------------|------|------|----------------------|------|-----------------------|------|------|------|
|                 |                           | V <sub>CC</sub><br>(V) |                                                              | T <sub>A</sub> = 25 °C<br>54HC and 74HC |      |      | -40 to 85 °C<br>74HC |      | -55 to 125 °C<br>54HC |      |      |      |
|                 |                           |                        |                                                              | Min.                                    | Typ. | Max. | Min.                 | Max. | Min.                  | Max. |      |      |
| V <sub>IH</sub> | High Level Input Voltage  | 2.0                    |                                                              | 1.5                                     |      |      | 1.5                  |      | 1.5                   |      | V    |      |
|                 |                           | 4.5                    |                                                              | 3.15                                    |      |      | 3.15                 |      | 3.15                  |      |      |      |
|                 |                           | 6.0                    |                                                              | 4.2                                     |      |      | 4.2                  |      | 4.2                   |      |      |      |
| V <sub>IL</sub> | Low Level Input Voltage   | 2.0                    |                                                              |                                         |      | 0.5  |                      | 0.5  |                       | 0.5  | V    |      |
|                 |                           | 4.5                    |                                                              |                                         |      | 1.35 |                      | 1.35 |                       | 1.35 |      |      |
|                 |                           | 6.0                    |                                                              |                                         |      | 1.8  |                      | 1.8  |                       | 1.8  |      |      |
| V <sub>OH</sub> | High Level Output Voltage | 2.0                    | V <sub>I</sub> =<br>V <sub>IH</sub><br>or<br>V <sub>IL</sub> | I <sub>O</sub> =-20 μA                  | 1.9  | 2.0  |                      | 1.9  |                       | 1.9  |      | V    |
|                 |                           | 4.5                    |                                                              |                                         | 4.4  | 4.5  |                      | 4.4  |                       | 4.4  |      |      |
|                 |                           | 6.0                    |                                                              |                                         | 5.9  | 6.0  |                      | 5.9  |                       | 5.9  |      |      |
|                 |                           | 4.5                    |                                                              | I <sub>O</sub> =-4.0 mA                 | 4.18 | 4.31 |                      | 4.13 |                       | 4.10 |      |      |
|                 |                           | 6.0                    |                                                              | I <sub>O</sub> =-5.2 mA                 | 5.68 | 5.8  |                      | 5.63 |                       | 5.60 |      |      |
| V <sub>OL</sub> | Low Level Output Voltage  | 2.0                    | V <sub>I</sub> =<br>V <sub>IH</sub><br>or<br>V <sub>IL</sub> | I <sub>O</sub> = 20 μA                  |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  | V    |
|                 |                           | 4.5                    |                                                              |                                         |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  |      |
|                 |                           | 6.0                    |                                                              |                                         |      | 0.0  | 0.1                  |      | 0.1                   |      | 0.1  |      |
|                 |                           | 4.5                    |                                                              | I <sub>O</sub> = 4.0 mA                 |      | 0.17 | 0.26                 |      | 0.33                  |      | 0.40 |      |
|                 |                           | 6.0                    |                                                              | I <sub>O</sub> = 5.2 mA                 |      | 0.18 | 0.26                 |      | 0.33                  |      | 0.40 |      |
| I <sub>I</sub>  | Input Leakage Current     | 6.0                    | V <sub>I</sub> = V <sub>CC</sub> or GND                      |                                         |      | ±0.1 |                      | ±1   |                       | ±1   | μA   |      |
| I <sub>CC</sub> | Quiescent Supply Current  | 6.0                    | V <sub>I</sub> = V <sub>CC</sub> or GND                      |                                         |      | 4    |                      | 40   |                       | 80   | μA   |      |

AC ELECTRICAL CHARACTERISTICS (C<sub>L</sub> = 50 pF, Input t<sub>r</sub> = t<sub>f</sub> = 6 ns)



| Symbol                               | Parameter                                | Test Conditions        |  | Value                                   |      |      |                      |      |                       | Unit |      |
|--------------------------------------|------------------------------------------|------------------------|--|-----------------------------------------|------|------|----------------------|------|-----------------------|------|------|
|                                      |                                          | V <sub>CC</sub><br>(V) |  | T <sub>A</sub> = 25 °C<br>54HC and 74HC |      |      | -40 to 85 °C<br>74HC |      | -55 to 125 °C<br>54HC |      |      |
|                                      |                                          |                        |  | Min.                                    | Typ. | Max. | Min.                 | Max. | Min.                  |      | Max. |
| t <sub>TLH</sub><br>t <sub>THL</sub> | Output Transition Time                   | 2.0                    |  |                                         | 30   | 75   |                      | 95   |                       | 110  | ns   |
|                                      |                                          | 4.5                    |  |                                         | 8    | 15   |                      | 19   |                       | 22   |      |
|                                      |                                          | 6.0                    |  |                                         | 7    | 13   |                      | 16   |                       | 19   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CLOCK - Q)       | 2.0                    |  |                                         | 92   | 180  |                      | 225  |                       | 270  | ns   |
|                                      |                                          | 4.5                    |  |                                         | 23   | 36   |                      | 45   |                       | 54   |      |
|                                      |                                          | 6.0                    |  |                                         | 20   | 31   |                      | 38   |                       | 46   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CLOCK - RCO)     | 2.0                    |  |                                         | 39   | 120  |                      | 150  |                       | 180  | ns   |
|                                      |                                          | 4.5                    |  |                                         | 13   | 24   |                      | 30   |                       | 36   |      |
|                                      |                                          | 6.0                    |  |                                         | 11   | 20   |                      | 26   |                       | 31   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (CLOCK - MAX/MIN) | 2.0                    |  |                                         | 120  | 240  |                      | 300  |                       | 360  | ns   |
|                                      |                                          | 4.5                    |  |                                         | 30   | 48   |                      | 60   |                       | 72   |      |
|                                      |                                          | 6.0                    |  |                                         | 26   | 41   |                      | 51   |                       | 61   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation Delay Time (LOAD - Q)        | 2.0                    |  |                                         | 108  | 205  |                      | 255  |                       | 310  | ns   |
|                                      |                                          | 4.5                    |  |                                         | 27   | 41   |                      | 51   |                       | 62   |      |
|                                      |                                          | 6.0                    |  |                                         | 23   | 35   |                      | 43   |                       | 53   |      |

**AC ELECTRICAL CHARACTERISTICS** ( $C_L = 50 \text{ pF}$ , Input  $t_r = t_f = 6 \text{ ns}$ )

| Symbol                                 | Parameter                                    | Test Conditions        |                        | Value                                   |            |      |                      |      |                       | Unit |      |
|----------------------------------------|----------------------------------------------|------------------------|------------------------|-----------------------------------------|------------|------|----------------------|------|-----------------------|------|------|
|                                        |                                              | V <sub>CC</sub><br>(V) |                        | T <sub>A</sub> = 25 °C<br>54HC and 74HC |            |      | -40 to 85 °C<br>74HC |      | -55 to 125 °C<br>54HC |      |      |
|                                        |                                              |                        |                        | Min.                                    | Typ.       | Max. | Min.                 | Max. | Min.                  |      | Max. |
| t <sub>PLH</sub><br>t <sub>PHL</sub>   | Propagation<br>Delay Time<br>(DATA - Q)      | 2.0                    |                        |                                         | 84         | 175  |                      | 220  |                       | 265  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 21         | 35   |                      | 44   |                       | 53   |      |
|                                        |                                              | 6.0                    |                        |                                         | 18         | 30   |                      | 37   |                       | 45   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub>   | Propagation<br>Delay Time<br>(ENABLE - RCO)  | 2.0                    |                        |                                         | 39         | 105  |                      | 130  |                       | 160  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 13         | 21   |                      | 26   |                       | 32   |      |
|                                        |                                              | 6.0                    |                        |                                         | 11         | 18   |                      | 22   |                       | 27   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub>   | Propagation<br>Delay Time<br>(D/U - RCO)     | 2.0                    |                        |                                         | 63         | 180  |                      | 225  |                       | 270  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 21         | 36   |                      | 45   |                       | 54   |      |
|                                        |                                              | 6.0                    |                        |                                         | 18         | 31   |                      | 38   |                       | 46   |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub>   | Propagation<br>Delay Time<br>(D/U - MAX/MIN) | 2.0                    |                        |                                         | 64         | 160  |                      | 200  |                       | 240  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 18         | 32   |                      | 40   |                       | 48   |      |
|                                        |                                              | 6.0                    |                        |                                         | 15         | 27   |                      | 34   |                       | 41   |      |
| f <sub>MAX</sub>                       | Maximum Clock<br>Frequency                   | 2.0                    |                        | 5                                       | 9          |      | 4                    |      | 3.4                   |      | MHz  |
|                                        |                                              | 4.5                    |                        | 25                                      | 37         |      | 20                   |      | 17                    |      |      |
|                                        |                                              | 6.0                    |                        | 30                                      | 44         |      | 24                   |      | 20                    |      |      |
| t <sub>w(H)</sub><br>t <sub>w(L)</sub> | Minimum Pulse<br>Width<br>(CLOCK)            | 2.0                    |                        |                                         | 40         | 100  |                      | 125  |                       | 150  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 10         | 20   |                      | 25   |                       | 30   |      |
|                                        |                                              | 6.0                    |                        |                                         | 9          | 17   |                      | 21   |                       | 26   |      |
| t <sub>w(L)</sub>                      | Minimum Pulse<br>Width<br>(LOAD)             | 2.0                    |                        |                                         | 36         | 75   |                      | 95   |                       | 110  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 9          | 15   |                      | 19   |                       | 22   |      |
|                                        |                                              | 6.0                    |                        |                                         | 8          | 13   |                      | 16   |                       | 19   |      |
| t <sub>s</sub>                         | Minimum Set-up<br>Time<br>(SI, PI - CK)      | 2.0                    |                        |                                         | 80         | 175  |                      | 220  |                       | 265  | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 20         | 35   |                      | 44   |                       | 53   |      |
|                                        |                                              | 6.0                    |                        |                                         | 17         | 30   |                      | 37   |                       | 45   |      |
| t <sub>s</sub>                         | Minimum Set-up<br>Time<br>(S0, S1 - CK)      | 2.0                    |                        |                                         | 16         | 50   |                      | 60   |                       | 75   | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 4          | 10   |                      | 12   |                       | 15   |      |
|                                        |                                              | 6.0                    |                        |                                         | 3          | 9    |                      | 11   |                       | 13   |      |
| t <sub>h</sub>                         | Minimum Hold<br>Time                         | 2.0                    |                        |                                         |            | 0    |                      | 0    |                       | 0    | ns   |
|                                        |                                              | 4.5                    |                        |                                         |            | 0    |                      | 0    |                       | 0    |      |
|                                        |                                              | 6.0                    |                        |                                         |            | 0    |                      | 0    |                       | 0    |      |
| t <sub>REM</sub>                       | Minimum<br>Removal Time                      | 2.0                    |                        |                                         | 12         | 50   |                      | 60   |                       | 5    | ns   |
|                                        |                                              | 4.5                    |                        |                                         | 3          | 10   |                      | 12   |                       | 15   |      |
|                                        |                                              | 6.0                    |                        |                                         | 3          | 9    |                      | 11   |                       | 13   |      |
| C <sub>IN</sub>                        | Input Capacitance                            |                        |                        |                                         | 5          | 10   |                      | 10   |                       | 10   | pF   |
| C <sub>PD</sub> (*)                    | Power Dissipation<br>Capacitance             |                        | for HC190<br>for HC191 |                                         | 111<br>112 |      |                      |      |                       |      | pF   |


(\*) C<sub>PD</sub> is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average operating current can be obtained by the following equation.  $I_{CC(opr)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}$

## SWITCHING CHARACTERISTICS TEST WAVEFORM

TEST CIRCUIT  $I_{cc}$  (Opr.)

## Plastic DIP16 (0.25) MECHANICAL DATA


| DIM. | mm   |       |      | inch  |       |       |
|------|------|-------|------|-------|-------|-------|
|      | MIN. | TYP.  | MAX. | MIN.  | TYP.  | MAX.  |
| a1   | 0.51 |       |      | 0.020 |       |       |
| B    | 0.77 |       | 1.65 | 0.030 |       | 0.065 |
| b    |      | 0.5   |      |       | 0.020 |       |
| b1   |      | 0.25  |      |       | 0.010 |       |
| D    |      |       | 20   |       |       | 0.787 |
| E    |      | 8.5   |      |       | 0.335 |       |
| e    |      | 2.54  |      |       | 0.100 |       |
| e3   |      | 17.78 |      |       | 0.700 |       |
| F    |      |       | 7.1  |       |       | 0.280 |
| I    |      |       | 5.1  |       |       | 0.201 |
| L    |      | 3.3   |      |       | 0.130 |       |
| Z    |      |       | 1.27 |       |       | 0.050 |



P001C

## Ceramic DIP16/1 MECHANICAL DATA


| DIM. | mm   |       |      | inch  |       |       |
|------|------|-------|------|-------|-------|-------|
|      | MIN. | TYP.  | MAX. | MIN.  | TYP.  | MAX.  |
| A    |      |       | 20   |       |       | 0.787 |
| B    |      |       | 7    |       |       | 0.276 |
| D    |      | 3.3   |      |       | 0.130 |       |
| E    | 0.38 |       |      | 0.015 |       |       |
| e3   |      | 17.78 |      |       | 0.700 |       |
| F    | 2.29 |       | 2.79 | 0.090 |       | 0.110 |
| G    | 0.4  |       | 0.55 | 0.016 |       | 0.022 |
| H    | 1.17 |       | 1.52 | 0.046 |       | 0.060 |
| L    | 0.22 |       | 0.31 | 0.009 |       | 0.012 |
| M    | 0.51 |       | 1.27 | 0.020 |       | 0.050 |
| N    |      |       | 10.3 |       |       | 0.406 |
| P    | 7.8  |       | 8.05 | 0.307 |       | 0.317 |
| Q    |      |       | 5.08 |       |       | 0.200 |



P053D


SO16 (Narrow) MECHANICAL DATA

| DIM. | mm         |      |      | inch  |       |       |
|------|------------|------|------|-------|-------|-------|
|      | MIN.       | TYP. | MAX. | MIN.  | TYP.  | MAX.  |
| A    |            |      | 1.75 |       |       | 0.068 |
| a1   | 0.1        |      | 0.2  | 0.004 |       | 0.007 |
| a2   |            |      | 1.65 |       |       | 0.064 |
| b    | 0.35       |      | 0.46 | 0.013 |       | 0.018 |
| b1   | 0.19       |      | 0.25 | 0.007 |       | 0.010 |
| C    |            | 0.5  |      |       | 0.019 |       |
| c1   | 45° (typ.) |      |      |       |       |       |
| D    | 9.8        |      | 10   | 0.385 |       | 0.393 |
| E    | 5.8        |      | 6.2  | 0.228 |       | 0.244 |
| e    |            | 1.27 |      |       | 0.050 |       |
| e3   |            | 8.89 |      |       | 0.350 |       |
| F    | 3.8        |      | 4.0  | 0.149 |       | 0.157 |
| G    | 4.6        |      | 5.3  | 0.181 |       | 0.208 |
| L    | 0.5        |      | 1.27 | 0.019 |       | 0.050 |
| M    |            |      | 0.62 |       |       | 0.024 |
| S    | 8° (max.)  |      |      |       |       |       |



## PLCC20 MECHANICAL DATA

| DIM. | mm   |      |       | inch  |       |       |
|------|------|------|-------|-------|-------|-------|
|      | MIN. | TYP. | MAX.  | MIN.  | TYP.  | MAX.  |
| A    | 9.78 |      | 10.03 | 0.385 |       | 0.395 |
| B    | 8.89 |      | 9.04  | 0.350 |       | 0.356 |
| D    | 4.2  |      | 4.57  | 0.165 |       | 0.180 |
| d1   |      | 2.54 |       |       | 0.100 |       |
| d2   |      | 0.56 |       |       | 0.022 |       |
| E    | 7.37 |      | 8.38  | 0.290 |       | 0.330 |
| e    |      | 1.27 |       |       | 0.050 |       |
| e3   |      | 5.08 |       |       | 0.200 |       |
| F    |      | 0.38 |       |       | 0.015 |       |
| G    |      |      | 0.101 |       |       | 0.004 |
| M    |      | 1.27 |       |       | 0.050 |       |
| M1   |      | 1.14 |       |       | 0.045 |       |



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A