



SAW Components

SAW RF filter for base stations

APT700


Series/type:	B5194
Ordering code:	B39731B5194U410
Date:	April 29,2014
Version:	2.1

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.


Application

- RF Rx filter for APT 700
- Usable passband 45MHz
- Unbalanced to unbalanced operation




Features

- Package size 3.0 x3.0 x 1.1 mm³
- Package code DCC6C
- RoHS compatible
- Approximate weight 0.037 g
- Ceramic Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- **Moisture Sensitive Level 1**
- Filter surface passivated



Pin configuration

- 2 Input
- 5 Output
- 1,3,4,6 Case grounded



SAW Components
B5194
SAW RF filter for base stations
725.5 MHz
Data sheet

Characteristics

 Temperature range for specification: $T = -40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$

 Terminating source impedance: $Z_S = 50\ \Omega$

 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ. @ 25 °C	max.	
Nominal frequency	f_N	—	725.5	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$				
703.0 ... 748.0 MHz		—	2.4	3.0	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
703.0 ... 748.0 MHz		—	0.7	1.5	dB
Return loss					
703.0 ... 748.0 MHz		10	12	—	dB
Absolute attenuation	α_{abs}				
50.0 ... 100.0 MHz		30	47	—	dB
430.0 ... 480.0 MHz		30	35	—	dB
480.0 ... 648.0 MHz		20	28	—	dB
785.0 ... 830.0 MHz		14	18	—	dB
936.0 ... 971.0 MHz		20	40	—	dB
1090.0 ... 1150.0 MHz		20	26	—	dB
1615.0 ... 1660.0 MHz		30	37	—	dB

SAW Components
B5194
SAW RF filter for base stations
725.5 MHz
Data sheet



Maximum ratings



Operable temperature range	T	−45/+125	°C	
Storage temperature range	T _{stg}	−45/+125	°C	
DC voltage	V _{DC}	6	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	machine model, 10 pulses
		350 ²⁾	V	human body model, 1 pulse
		1000 ³⁾	V	charge device model
Input power at				
703.0 ... 748.0 MHz	P _{IN}	25	dBm	CW @ 85°C, 48 hrs
703.0 ... 748.0 MHz	P _{IN}	20	dBm	CW @ 85°C, 100000 hrs

¹⁾ acc. to JESD22-A115B (machine model), +/- 10 pulses.

²⁾ acc. to JESD22-A114F (human body model), +/- 1 pulse.

³⁾ acc. to JESD22-C101E (charge device model).

Transfer function

Transfer function (wideband)


Data sheet
SMD
Smith chart
 S_{11} function

 S_{22} function


SAW Components	B5194
SAW RF filter for base stations	725.5 MHz

Data sheet



References

Type	B5194
Ordering code	B39731B5194U410
Marking and package	C61157-A7-A67
Packaging	F61074-V8228-Z000
Date codes	L_1126
S-parameters	B5194_NB.s2p,B5194_WB.s2p see file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011, on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("Directive") with due regard to the application of exemptions as per Annex III of the Directive in certain cases.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Systems, Acoustics, Waves Business Group
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2014. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, TFAP, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.