258FSB360XEM

PHOTOFLASH ALUMINUM ELECTROLYTIC CAPACITORS

Parts are RoHS compliant

Date code when parts became RoHS: 1327

APPLICATIONS: Photoflash, strobes, Security systems

ELECTRICAL SPECIFICATIONS

Capacitance: 2500 uF
Dissipation Factor: 0.15 Max at 120 Hz and 20°C
Temperature Range: -20°C to +55°C
Impedance: N/A

Tolerance: -20 %, +50 %
WVDC: 360 Volts DC
SVDC: 390 Volts DC
Ripple Current: at and
Impedance Ratios:- and - -

Leakage Current: 1*C
2500 uA after 5 Minutes

Charge/discharge: 5000 charge/discharge cycles at rated voltage & 5~35C repeating every 30 seconds thru a Xe tube having a discharge resistance of 0.7 to 1 Ohm
Capacitance Change: ≤10% of initial measured value
Dissipation Factor: ≤150% of maximum specified value
Leakage Current: ≤150% of maximum specified value

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
1	1	1	1	1	1

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1	1	1	1	1	1	1	0

PHYSICAL DIMENSIONS

Diameter (D): 35 mm + 1 mm
Length (L): 80 mm + 2 mm
Lead Spacing (S): 10 mm +/- 1 mm
Coating: BlackPVC sleeving

Lead Wire Diameter (d): 4 mm +/- 0.5 mm
Lead Length: 7 mm +/- 1 mm
Lead Finish: Matte Tin



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847) 675-1760 FAX (847) 673-2850
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.illcap.com.hk
© Copyright 2019 Illinois Capacitor. An affiliate of Cornell Dubilier, All Rights Reserved