ALPHA & OMEGA SEMICONDUCTOR

AO7801
Dual P-Channel Enhancement Mode Field Effect Transistor

General Description


The AO7801 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge, and operation with gate voltages as low as 1.8V, in the small SOT323 footprint. It can be used for a wide variety of applications, including load switching, low current inverters and low current DC-DC converters. It is ESD protected to 2KV HBM.


Features

V_{DS} (V) = -20V
I_D = -0.6A (V_{GS} = -4.5V)
$R_{DS(ON)}$ < 520mΩ (V_{GS} = -4.5V)
$R_{DS(ON)}$ < 700mΩ (V_{GS} = -2.5V)
$R_{DS(ON)}$ < 950mΩ (V_{GS} = -1.8V)

Green Product

SC-70-6
(SOT-323)
Top View





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±8	V
Continuous Drain Current [A]	T_A=25°C	I_D	-0.6	A
	T_A=70°C		-0.48	
Pulsed Drain Current [B]		I_{DM}	-3	
Power Dissipation [A]	T_A=25°C	P_D	0.3	W
	T_A=70°C		0.19	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	360	415	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		400	460	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	300	350	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-20			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-16V, V_{GS}=0V			-1	µA
		T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±8V			±10	µA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA	-0.5	-0.6	-0.9	V
$I_{D(ON)}$	On state drain current	V_{GS}=-4.5V, V_{DS}=-5V	-3			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-4.5V, I_D=-0.6A		400	520	mΩ
		T_J=125°C		542	700	
		V_{GS}=-2.5V, I_D=-0.5A		540	700	mΩ
		V_{GS}=-1.8V, I_D=-0.4A		700	950	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-0.6A		1.7		S
V_{SD}	Diode Forward Voltage	I_S=-0.5A,V_{GS}=0V		-0.86	-1	V
I_S	Maximum Body-Diode Continuous Current				-0.4	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-10V, f=1MHz		114	140	pF
C_{oss}	Output Capacitance			17		pF
C_{rss}	Reverse Transfer Capacitance			14		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		12	17	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=-4.5V, V_{DS}=-10V, I_D=-0.6A		1.44	1.8	nC
Q_{gs}	Gate Source Charge			0.14		nC
Q_{gd}	Gate Drain Charge			0.35		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-4.5V, V_{DS}=-10V, R_L=16.7Ω, R_{GEN}=3Ω		6.5		ns
t_r	Turn-On Rise Time			6.5		ns
$t_{D(off)}$	Turn-Off DelayTime			18.2		ns
t_f	Turn-Off Fall Time			5.5		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-0.6A, dI/dt=100A/µs		10	13	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-0.6A, dI/dt=100A/µs		3		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The value in any a given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.
B: Repetitive rating, pulse width limited by junction temperature.
C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.
D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80 µs pulses, duty cycle 0.5% max.
E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The SOA curve provides a single pulse rating.
Rev2: May 2012

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance