

Power Schottky Rectifier - 30Amp 120Volt☐ **Features**

- Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- High Junction Temperature Capability
- Low forward voltage, high current capability
- High surge capacity
- Low power loss, high efficiency
- ESD performance human body mode > 6 KV
- Halogen-Free

☐ **Application**

- AC/DC Switching Adaptor and other Switching Power Supply

☐ **Absolute maximum ratings**

Symbol	Ratings	Unit	Conditions
I _{F(AV)}	30	A	Average Forward Current
V _{RRM}	120	V	Repetitive Peak Reverse Voltage
I _{FSM}	350	A	Peak Forward Surge Current
V _F	0.69	V	Forward Voltage Drop
T _j , T _{stg}	-50 to +175	°C	Operating and Storage Temperature

☐ **Electrical characteristics**

Parameters	Symbol	Ratings	Conditions
Maximum Instantaneous Forward Voltage	V _F		Per Leg at I _F = 15A
		0.88V	T _c = 25°C
		0.69V	T _c = 125°C
Maximum Reverse Leakage Current	I _R		Per Leg at V _R = 120V
		0.05mA	T _c = 25°C
		10mA	T _c = 125°C
Typical Thermal Resistance,Junction to Case	R _{θ(j-c)}		Per Leg
		2.2 °C/W	TO-220AB
		4.5 °C/W	ITO-220AB

October 2011 / Rev.6.7




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-repetitive Surge Current




Figure 3. Typical Reverse Characteristics




Figure 4. Typical Forward Characteristics






Figure 5. Typical Junction Capacitance

MBR30B120CTH



TO-220AB



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.579	.606	14.70	15.40	
B	.392	.411	9.95	10.45	
C	.114	.126	2.90	3.20	
D	.248	.272	6.30	6.90	
E	.325	.350	8.25	8.90	
F	.153	.173	3.90	4.40	
G	.492	.551	12.50	14.00	
H	.096	.108	2.45	2.75	
I	.028	.039	0.70	1.00	
J	.010	.022	0.25	0.55	
K	.146	.157	3.70	4.00	
L	.167	.187	4.25	4.75	
M	.045	.057	1.15	1.45	
N	.089	.114	2.25	2.90	
O	.047	.055	1.20	1.40	

MBR30B120FCTH

ITO-220AB



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.577	.600	14.65	15.25	
B	.386	.406	9.80	10.30	
C	.106	.122	2.70	3.10	
D	.258	.274	6.55	6.95	
E	.315	.331	8.00	8.40	
F	.110	.161	2.80	4.10	
G	.508	.551	12.90	14.00	
H	.089	.106	2.25	2.70	
I	.020	.028	0.50	0.70	
J	.020	.028	0.50	0.70	
K	.120	.138	3.05	3.50	
L	.169	.185	4.30	4.70	
M	.039	.051	1.00	1.30	
N	.079	.112	2.00	2.85	
O	.043	.055	1.10	1.40	