

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [34708-2007](#)
Status: **Active**
Overview: [Stac64™ Single, Multi-Pocket and Hybrid Header System](#)
Description: [Stac64™ 2 Bay Right Angle Headers, 36 Circuits, Bay A 16 Circuit Signal Header, Polarization C, Brown; Bay B 20 Circuit Signal Header, Polarization C, Tray](#)

Documents:

| | |
|--|--|
| 3D Model | Application Specification AS-34729-020 (PDF) |
| Drawing (PDF) | RoHS Certificate of Compliance (PDF) |
| Product Specification PS-31372-100 (PDF) | Product Literature (PDF) |
| Product Specification PS-34729-020 (PDF) | |

General

| | |
|-----------------------------|--|
| Product Family | PCB Headers |
| Series | 34708 |
| Application | Power, Wire-to-Board |
| Comments | Bay A 16 Circuits Stac64™ Right Angle Signal Header, Polarization C. Bay B 20 Circuits Stac64™ Right Angle Signal Header, Polarization C |
| Overview | Stac64™ Single, Multi-Pocket and Hybrid Header System |
| Product Literature Order No | 987650-4561 |
| Product Name | Stac64™ |
| UPC | 887191467702 |

Physical

| | |
|--------------------------------|--------------------------------|
| Breakaway | No |
| Circuits (Loaded) | 36 |
| Circuits (maximum) | 36 |
| Color - Resin | Brown |
| Durability (mating cycles max) | 10 |
| First Mate / Last Break | No |
| Glow-Wire Compliant | No |
| Guide to Mating Part | No |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Nickel |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 16.117/g |
| Number of Rows | 2 |
| Orientation | Right Angle |
| PC Tail Length | 3.36mm |
| PCB Locator | Yes |
| PCB Retention | None |
| PCB Thickness - Recommended | 1.57mm |
| Packaging Type | Tray |
| Pitch - Mating Interface | 2.54mm |
| Pitch - Termination Interface | 2.54mm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | Yes |
| Shrouded | Yes |
| Stackable | No |
| Surface Mount Compatible (SMC) | N/A |
| Temperature Range - Operating | -40°C to +100°C |

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Low-Halogen Status

Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[34708Series](#)

Mates With

[31408](#) USCAR 2.54mm (.100") Pitch Receptacle, [31372](#) 5.25mm (.206") Pitch Hybrid Receptacle Assembly, [34729](#) 2.54mm (.100") Pitch [Stac64™](#) Right Angle Receptacle

Termination Interface: Style

Through Hole

Electrical

Current - Maximum per Contact
Voltage - Maximum

Contact Molex
500V

Material Info

Reference - Drawing Numbers

Application Specification
Product Specification
Sales Drawing

AS-34729-020
PS-31372-100, PS-34729-020
SD-34708-200

This document was generated on 09/16/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION