

## Ceramic Surface Mount Crystal

The SM5 series incorporates a sub-miniature AT-cut strip crystal resonator housed in a standard 7.0x5.0x1.3 mm ceramic package. These compact crystals are ideal for surface mount, densely-populated PCB applications.


**SM5**

**RoHS Compliant**

**Specifications:**

<b>Frequency Range:</b>	8.0 MHz ~ 45 MHz	Fundamental
	36 MHz ~ 121 MHz	Overtone
<b>Operating Temperature:</b>	0°C ~ +50°C	-A
	-10°C ~ +60°C	-B
	-20°C ~ +70°C	-C
	-40°C ~ +85°C	-L
<b>Storage Temperature:</b>	-55°C ~ +125°C	
<b>Frequency Tolerance:</b>	± 50 ppm	-50
(at 25°C)	± 30 ppm	-30
	± 20 ppm	-20
	± 10 ppm	-10
<b>Frequency Stability:</b>	± 50 ppm	-50
(over temperature range)	± 30 ppm	-30
	± 20 ppm	-20
	± 10 ppm	-10
<b>Circuit Condition:</b>	10 pF ~ 32 pF or series	
<b>Equivalent Series Resistance:</b>	Maximum resistance corresponds to frequency. Please see ESR table.	
<b>Drive Level:</b>	0.1 mW max	
<b>Shunt Capacitance:</b>	7 pF max	
<b>Aging:</b>	± 3 ppm max per year	
<b>Optional Features:</b>	Fundamental	-F
	3 <sup>rd</sup> , 5 <sup>th</sup> , 7 <sup>th</sup> O.T.	-3,5,7
	Tape & Reel	-TR

**SM5**



All dimensions are in mm

**Ordering Information**

Product name + CL + Operating Temperature Range + Tolerance + Stability + Other Code + Frequency.

i.e. SM5-20-C-30-30-F-24.000MHz

Note:

1. Other frequencies, tolerances, stabilities, and operating temperature ranges available. Consult VTC Support for specific requirements.
2. Not all combinations of the above tolerances, stabilities, and temperature ranges are available. Consult VTC Support if your requirement is not standard.
3. All specifications subject to change without notice.