



K1526D Series


9x14 mm, 5.0 Volt, CMOS/TTL, VCXO



- Former **Champion** Product
- Phase-Locked Loops (PLL's), Clock Recovery, Reference Signal Tracking, Synthesizers, Frequency Modulation/Demodulation



SUGGESTED SOLDER PAD LAYOUT



Pin Connections

PIN	FUNCTION
1	Voltage Control
2	Ground & Gnd Plane
3	Output
4	+Vdd

Ordering Information

Product Series	K1526D	X	X	-R	00.0000 MHz
Model Selection	A: $\pm 100 - \pm 150$ ppm Pull*	D: $\pm 80 - \pm 130$ ppm Pull*			
Temperature Range	Blank: 0°C to $+70^{\circ}\text{C}$	M: -40°C to $+85^{\circ}\text{C}$			
RoHS Compliance	Blank: non-RoHS compliant part	-R: RoHS compliant part			
Frequency (customer specified)					

* Above 40 MHz, pull is ± 100 ppm or ± 80 ppm minimum (no maximum)

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Frequency Range	F	2		40	MHz	
Operating Temperature	T _A	(See ordering information)				
Storage Temperature	T _S	-40		+125	$^{\circ}\text{C}$	
Frequency Stability Overall	$\Delta F/F$	Inclusive of Calibration, Temperature, Voltage, Load, and Aging				
0 $^{\circ}\text{C}$ to +70 $^{\circ}\text{C}$				± 25	ppm	
-40 $^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$				± 50	ppm	
Aging 1 st Year		-3		+3	ppm	
Thereafter (per year)		-1		+1	ppm	
Pullability/APR		(See ordering information)				
Control Voltage	V _C	0.5	2.5	4.5	V	
Linearity				5	%	Positive Monotonic Slope
2.000 to 33.000 MHz				10	%	
33.001 to 160.000 MHz						
Modulation Bandwidth	f _m	20			KHz	$\pm 3\text{dB}$
Input Impedance	Z _{in}	50k			Ohms	@ 10 kHz
Input Voltage	V _{dd}	4.5	5.0	5.5	V	
Input Current	I _{dd}			26	mA	
Output Type						HCMOS/TTL
Load		5 TTL or 15 pF HCMOS				See Note 1
Symmetry (Duty Cycle)						See Note 2
TTL & CMOS < 33 MHz		45		55	%	
CMOS ≥ 33 MHz		40		60	%	
Logic "1" Level	V _{oh}	4.5			V	
Logic "0" Level	V _{ol}			0.5	V	
Output Current				± 16	mA	
Rise/Fall Time	T _r /T _f			4	ns	
Start up Time				10	ms	
Phase Jitter @ 26 MHz	ϕ_J		4		ps RMS	Integrated 12 kHz – 20 MHz
Phase Noise (Typical) @ 26 MHz		10 Hz	100 Hz	1 kHz	10 kHz	100 kHz
		-65	-95	-115	-130	-140
						dBc/Hz
Mechanical Shock		Per MIL-STD-202, Method 213, Condition C (100 g's, 6 ms duration, ½ sinewave)				
Vibration		Per MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)				
Hermeticity		Per MIL-STD-202, Method 112, (1x10 ⁻⁸ atm. cc/s of Helium)				
Thermal Cycle		Per MIL-STD-883, Method 1010, Condition B (-55 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$, 15 min. dwell, 10 cycles)				
Solderability		Per EIAJ-STD-002				
Soldering Conditions		+240 $^{\circ}\text{C}$ max. for 10 secs.				

1. TTL load – see load circuit diagram #1. HCMOS load – see load circuit diagram #2.
2. Symmetry is measured at 1.4 V with TTL load, and at 50% V_{dd} with HCMOS load.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.