



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon6T, UL94V-0
PIN Phosphoric bronze Tin-plated
Solder tads Phosphoric bronze Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-CB1.25-2AWT	1.25	7.65
HC-CB1.25-3AWT	2.50	8.90
HC-CB1.25-4AWT	3.75	10.15
HC-CB1.25-5AWT	5.00	11.40
HC-CB1.25-6AWT	6.25	12.65
HC-CB1.25-7AWT	7.50	13.90
HC-CB1.25-8AWT	8.75	15.15
HC-CB1.25-9AWT	10.00	16.40
HC-CB1.25-10AWT	11.25	17.65
HC-CB1.25-11AWT	12.50	18.90
HC-CB1.25-12AWT	13.75	20.15

PCB LAYOUT

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生		料号 PART NO.	HC-CB1.25-NAWT	版本 REV.	A								
			X.±0.25	X.*±2°		2013.07.01	张名					品名 TITLE	1.25超薄贴片 WAFER SMT TYPE	页次 SHEET	1/1				
			.X±0.20	.X*±1°												2013.07.03	张名	客户料号 CUTW. NO.	
			.XX±0.15	.XX*±0.5°															
.XXX±0.10	.XXX*±0.5°	单位 UNITS	MM	比例 SCALE	1:1			深圳市华灿天禄电子有限公司											