

Hi-Q® High RF Power MLC Surface Mount Capacitors

For 600V to 7200V Application



PRODUCT OFFERING

Hi-Q®, high RF power, surface mount MLC capacitors from AVX Corporation are characterized with ultra-low ESR and dissipation factor at high frequencies. They are designed to handle high power and high voltage levels for applications in RF power amplifiers, inductive heating, high magnetic field environments (MRI coils), medical and industrial electronics.


HOW TO ORDER

HQCC	A	A	271	J	A	T	1	A
AVX Style	Voltage	Temperature Coefficient	Capacitance Code	Capacitance Tolerance	Test Level	Termination*	Packaging	Special Code
HQCC	600V/630V = C	C0G = A	(2 significant digits + no. of zeros)	C = $\pm 0.25\text{pF}$ (<13pF)	A = Standard	1 = Pd/Ag	1 = 7" Reel	A = Standard
HQCE	1000V = A		Examples:	D = $\pm 0.50\text{pF}$ (<25pF)		T = Plated	3 = 13" Reel	
	1500V = S		4.7 pF = 4R7	F = $\pm 1\%$ ($\geq 25\text{pF}$)		Ni and Sn	9 = Bulk	
	2000V = G		10 pF = 100	G = $\pm 2\%$ ($\geq 13\text{pF}$)		(RoHS Compliant)		
	2500V = W		100 pF = 101	J = $\pm 5\%$		J = 5% Min Pb		
	3000V = H		1,000 pF = 102	K = $\pm 10\%$				
	4000V = J			M = $\pm 20\%$				
	5000V = K							
	7200V = M							

Contact factory for availability of Termination and Tolerance options for Specific Part Numbers.

DIMENSIONS millimeters (inches)

STYLE	HQCC	HQCE
(L) Length	5.84 $\pm$ 0.51 (0.230 $\pm$ 0.020)	9.4 $\pm$ 0.51 (0.370 $\pm$ 0.020)
(W) Width	6.35 $\pm$ 0.51 (0.250 $\pm$ 0.020)	9.9 $\pm$ 0.51 (0.390 $\pm$ 0.020)
(T) Thickness Max.	3.3 max. (0.130 max.)	3.3 max. (0.130 max.)
(t) terminal	0.64 $\pm$ 0.38 (0.025 $\pm$ 0.015)	0.64 $\pm$ 0.38 (0.025 $\pm$ 0.015)



DIELECTRIC PERFORMANCE CHARACTERISTICS

Capacitance Range	3.3pF to 6,800pF (25°C, 1.0 $\pm$ 0.2 Vrms at 1kHz, for $\leq$ 1000 pF use 1MHz)
Capacitance Tolerances	$\pm 0.25\text{pF}$, $\pm 0.50\text{pF}$, $\pm 1\%$, $\pm 2\%$, $\pm 5\%$, $\pm 10\%$, $\pm 20\%$
Dissipation Factor 25°C	0.1% Max (+25°C, 1.0 $\pm$ 0.2 Vrms at 1kHz, for $\leq$ 1000 pF use 1MHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	C0G: 0 $\pm$ 30 ppm/°C (-55°C to +125°C)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000, 5000, 7200VDC
Insulation Resistance	100K M Ω min. @ +25°C and 500VDC 10K M Ω min. @ +125°C and 500VDC
Dielectric Strength	Minimum 120% of rated WVDC





HIGH VOLTAGE CAPACITANCE VALUES (pF)

Style	600/630 WDC min./max.	1000 WVDC min./max.	1500 WVDC min./max.	2000 WVDC min./max.	2500 WVDC min./max.	3000 WVDC min./max.	4000 WVDC min./max.	5000 WVDC min./max.	7200 WVDC min./max.
HQCC	2,200 - 2,700	1,500 - 1,800	820 - 1,200	470 - 680	330 - 390	3.3 - 270			
HQCE	5,600 - 6,800	3,300 - 4,700	2,200 - 2,700	1,200 - 1,800	820 - 1,000	470-680	220-390	120 - 180	3.3 - 100

Hi-Q® High RF Power MLC Capacitors



PERFORMANCE CHARACTERISTICS




Hi-Q® High RF Power MLC Capacitors




PERFORMANCE CHARACTERISTICS


Typical Series Resonant Frequency vs. Capacitance
HQCE and HQLE



Typical ESR vs. Capacitance
HQCE and HQLE



Typical Quality Factor vs. Capacitance
HQCE and HQLE



Maximum RMS Current vs. Capacitance
HQCE and HQLE

