



Pin	Dim.(mm)		Order Code
	A	B	
2X05	4.00	8.00	M40-1200500
2X06	5.00	9.00	M40-1200600
2X07	6.00	10.00	M40-1200700
2X08	7.00	11.00	M40-1200800
2X09	8.00	12.00	M40-1200900
2X10	9.00	13.00	M40-1201000
2X12	11.00	15.00	M40-1201200
2X15	14.00	18.00	M40-1201500
2X20	19.00	23.00	M40-1202000
2X25	24.00	28.00	M40-1202500

SPECIFICATIONS:
 MATERIAL(HALOGEN FREE):
 NYLON 66, UL94V-0 (WHITE)
 ELECTRICAL:
 CURRENT RATING: 1A AC/DC
 VOLTAGE RATING: 50V AC/DC
 WITHSTAND VOLTAGE: 500V AC/MINUTE
 CONTACT RESISTANCE: 20 mΩ MAX.
 INSULATION RESISTANCE: 100 MΩ MIN.
 ENVIRONMENTAL:
 TEMPERATURE RANGE: -25°C TO +85°C

Leo	3	08.02.18	A530
Allan	2	03.05.07	A041
Allan	1	01.08.06	--

ORDER CODE

M40-120 XX 00

NO. OF WAYS PER ROW

NOTE: ALL DIMENSIONS AND NOTES MARKED * ARE CRITICAL AND MUST BE CHECKED IN ACCORDANCE WITH QUALITY DOC. QI-02A

NAME	ISS.	DATE	C/NOTE
APPROVED:	B.Lim		
CHECKED:	D.P		
DRAWN:	Leo		
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

HARWIN USA
 TEL: 603 893 5376
 FAX: 603 893 5396
 mis@harwin.com

HARWIN Europe (UK)
 TEL: 023 9231 4545
 FAX: 023 9231 4590
 mis@harwin.co.uk

HARWIN Asia
 TEL: +65 6 779 4909
 FAX: +65 6 779 3868
 mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
 X. = ±0.30mm
 X.X = ±0.25mm
 X.XX = ±0.15mm
 X.XXX = ±0.08mm
 ANGLES = ±3°
 UNLESS STATED

MATERIAL:
 SEE NOTES

FINISH:
 SEE NOTES

S/AREA: mm²

TITLE:
 1.00mm PITCH WIRE TO BOARD CONNECTOR

DRAWING NUMBER:
 M40-120 XX 00

SHT
 1
 OF
 1