


Plastic Point Source Infrared Emitting Diode Type OP245PS



Features

- Point source irradiance pattern
- Wavelength matched to silicon's peak response
- Fast switching speed
- Side-looking package for space limited applications

Description

The OP245PS is an 850 nm, infrared emitting diode molded in IR transmissive amber-tinted epoxy packages. The side-looking package is for use in PC board mounted slotted switches or as easily mounted interrupt detectors.

The stable V_F vs. Temperature characteristic make them ideal for applications where voltage is limited (such as battery operation).

The low t_r/t_f make them ideal for high speed operations.

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Reverse Voltage	2.0 V
Continuous Forward Current	50 mA
Peak Forward Current (2 μs pulse width, 0.1% duty cycle)	1.0 A
Storage and Operating Temperature Range	-40°C to $+100^\circ\text{C}$
Lead Soldering Temperature [1/16 inch (1.6mm) from case for 5 sec. with soldering iron]	260°C ⁽¹⁾
Power Dissipation	100 mW ⁽²⁾

NOTES:

- (1) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering. A maximum of 20 grams force may be applied to the leads when soldering.
- (2) Derate linearly 1.33 mW/ $^\circ\text{C}$ above 25°C .
- (3) $E_{e(\text{APT})}$ is a measurement of the average apertured radiant incidence upon a sensing area 0.180" (4.57 mm) in diameter, perpendicular to and centered on the mechanical axis of the lens, and 0.653" (16.6 mm) from the measurement surface. $E_{e(\text{APT})}$ is not necessarily uniform within the measured area.

Type OP245PS

Electrical Characteristics ($T_A = 25^\circ \text{C}$ unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
$E_{e(APT)}$	Apertured Irradiance	.10		.90	mW/cm^2	$I_F = 20 \text{ mA}^{(3)}$
V_F	Forward Voltage			1.80	V	$I_F = 20 \text{ mA}$
I_R	Reverse Current			20	μA	$V_R = 2 \text{ V}$
λ_p	Wavelength at Peak Emission		850		nm	$I_F = 20 \text{ mA}$
B	Spectral Bandwidth Between Half Power Points		50		nm	$I_F = 20 \text{ mA}$
θ_{HP}	Emission Angle at Half Power		$\pm 18^\circ$		Deg.	$I_F = 20 \text{ mA}$
t_r	Rise Time		10		ns	$I_{F(PK)} = 20 \text{ mA}$
t_f	Fall Time		10		ns	$PW = 10 \mu\text{s}$, D.C. = 10%

INFRARED
EMITTING
DIODES

Optek reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Optek Technology, Inc. 1215 W. Crosby Road Carrollton, Texas 75006 (972)323-2200 Fax (972)323-2396