

High sensitive triggering levels, the IPS6008 series SCRs is suitable for all applications, where the available gate current is limited, such as capacitive discharge ignitions, motor control in kitchen aids, overvoltage crowbar protection in low power supplies…



TO-92



MAIN FEATURES

Symbol	Value	Unit
$I_{T(AV)}$	0.8	A
V_{DRM} / V_{RRM}	600	V
I_{GT}	≤ 200	uA

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage Junction Temperature Range Operating Junction Temperature Range	Tstg Tj	-40 to +150 -40 to +125	℃
Repetitive Peak Off-state Voltage Tj = 25℃ Repetitive Peak Reverse Voltage Tj = 25℃	V_{DRM} V_{RRM}	600 600	V
RMS on–state current (180 conduction angle) Tc =77 ℃	$I_{T(RMS)}$	0.8	A
Average on-state current (180 conduction angle) Tc =77 ℃	$I_{T(AV)}$	0.5	A
Non repetitive surge peak on–state Current (Tj = 25℃) tp = 10 ms tp = 8.3 ms	I_{TSM}	 9 10	A
I^2t Value for fusing tp = 10ms	I^2t	0.415	A^2s
Peak gate current tp = 20us, Tj = 110 ℃	I_{GM}	0.2	A
Average gate power dissipation Tj = 110 ℃	$P_{G(AV)}$	0.1	W

4F, Cheong won B/D, 269 Hyoje-dong, Jongno-gu, Seoul, 110-480 Korea
Tel : +82-70-7574-2839, Fax : +82-2-6280-6382, sales@ipsemiconductor.com

ELECTRICAL CHARACTERISTICS (Tj = 25 ℃ unless otherwise specified)

Symbol	Test Condition		IPS6008-xxU				Unit
			03	05	06	08	
I_{GT}	V_D = 6V R_L = 100Ω	MIN MAX	10 30	20 50	30 60	50 80	uA
V_{GT}		TYP MAX	0.6 0.8				V
V_{GD}	V_D=V_{DRM}, R_L=3.3KΩ, R_{GK} = 1KΩ Tj = 110 ℃	MIN	0.2				V
I_L	I_G = 1mA R_{GK} = 1KΩ	MAX	6				mA
I_H	I_T = 50mA R_{GK} = 1KΩ	MAX	5				mA
V_{TM}	I_T = 1A t p = 380uS Tj = 25 ℃	TYP MAX	1.3 1.7				V/us
dV/dt	V_D = 67% V_{DRM} R_{GK} = 1KΩ Tj = 110 ℃	MIN	10				V/us
I_{DRM}	V_D = V_{DRM} R_{GK} = 1KΩ Tj = 25 ℃	MAX	5				uA
	V_D = V_{DRM} R_{GK} = 1KΩ Tj = 110 ℃	MAX	0.1				mA
I_{RRM}	V_R = V_{RRM} R_{GK} = 1KΩ Tj = 25 ℃	MAX	5				uA
	V_D = V_{RRM} R_{GK} = 1KΩ Tj = 110 ℃	MAX	0.1				mA


Please ask the IGT values to our sales if you want to get another values.


THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
R_{th} (j – c)	Junction to case	TO-92	75	℃/W


PACKAGE MECHANICAL DATA

TO-92





SECTION X-X



Ref	Dimensions			
	Millimeters		Inches	
	Min	Max	Min	Max
A	4.45	5.2	0.175	0.205
B	4.32	5.33	0.170	0.210
C	3.18	4.19	0.125	0.165
D	0.407	0.533	0.016	0.021
G	1.15	1.39	0.045	0.055
H	2.42	2.66	0.095	0.105
J	0.39	0.50	0.015	0.020
K	12.70	-	0.500	-
N	2.04	2.66	0.080	0.105
P	-	2.54	-	0.100
V	3.43	-	0.135	-

FIG.1: Maximum power dissipation versus RMS on-state current(full cycle)




FIG.2: RMS on-state current versus case temperature(full cycle)




FIG.3: On-state characteristics (maximum values)




FIG.4: Surge peak on-state current versus number of cycles.




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp<10ms.




FIG.6: Relative variation of gate trigger current,holding current and latching current versus junction temperature(typical values).

