


SBC



BA-0951

ATX MB supports Intel® Xeon® E3 V3 CPU with VGA/ DP/ Audio/ 2LAN/ 6COM

Features :

- LGA1150 Intel® Xeon® E3 V3 Processor
- Equipped with C226 Chipset
- Memory support four DDR3/DDR3L DIMM socket 1333/1600 up to 32GB (support ECC, non-ECC)
- Support Dual Gigabit Ethernet
- Support SATA RAID 0, 1, 5, 10
- Expansion Slots for two PCIe(8x), four PCIe(1x), Mini PCIe
- Support USB 3.0



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714- 996-7200 FAX: +1-714- 996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.


OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>



ISO CERTIFIED
9001 14001

BA-0951

ATX MB supports Intel® Xeon® E3 V3 CPU with VGA/ DP/ Audio/ 2LAN/ 6COM



Specifications

System	
CPU Support	Intel® Xeon® E3 V3 Processor
CPU Frequency	3.2~3.5GHz
Chipset	Intel® PCH C226
DRAM	4 x 240-pin DDR3 DIMM, support dual -channel 1333/1600Hz SDRAM ECC and Non-ECC Unbuffered DIMM (system max. 32GB)
BIOS	AMI BIOS
Watchdog	1~255 secs Watchdog timer selectable
Power Supply	Support ATX Power
Power Requirement	+5V, +12V, -12V,+3.3V, +5VSB
Dimension	305 mm x 244 mm (12" x 9.6")
Certificate	FCC / CE

I/O Chipset

SATA Interface	6 x SATA III (6.0Gb/s), (Raid 0,1,10,5)
Expansion BUS	2 x PCIe(8x) , 4 x PCIe(1x)
TPM	TPM1.2 with 20-pin header on board for TPM (Trusted Platform Module)
Serial Port	6 x COM port, COM 1/3/4/5/6 for RS-232, COM 2 for RS-232/422/485
Parallel Port	1 x parallel port (SPP/EPP/ECP)
Keyboard	PS/2 Connector, with mini DIN connector

Mouse	PS/2 Connector, with mini DIN connector
LAN	LAN 1: Intel® I217-LM (10/100/1000 Mbps) LAN 2: Intel® I210-AT (10/100/1000 Mbps) Support Wake-on-LAN with ATX power
Audio	High Definition Audio; Realtek 81866AD-I with Mic / Line-In / Line-Out
DI/O	4 in / 4 out
USB	8 x USB 2.0, 4 x USB 3.0

Display

Graphics	Build-in processor, share system memory Support 1 x VGA, 3 x Display port
-----------------	--

*Discrete graphic card is necessary for display if the chosen CPU doesn't have integrated graphics support.

Environment

Operation Temp.	0° ~ 60° C (32° ~ 140° F)
Storage Temp.	- 40° ~ 85° C (- 40° ~ 185° F)
Humidity	Operation humidity 5 ~ 90% (non-condensing)

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

Ordering Information

BA-0951RA-00P	ATX MB with Intel® Xeon® E3V3 CPU(LGA1150)+C226, DDR3/VGA/3DP/2LAN/6COM/Raid
----------------------	---

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd.
All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in May 2013.