# C20L100CT


**20A Trench Schottky Rectifier**

## ■ Features

- Low forward voltage drop.
- Excellent high temperature stability.
- Fast switching capability.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228


## ■ Outline

TO-220AB




| symbol | Dimensions in inches(millimeters) | |
|---|---|---|
| | Min | Max |
| A | 0.398(10.1) | 0.406(10.3) |
| B | 0.236(6.0) | 0.252(6.4) |
| C | 0.579(14.7) | 0.594(15.1) |
| D | 0.543(13.8) | 0.551(14.0) |
| E | 0.143(3.63) | 0.159(4.03) |
| F | 0.104(2.64) | 0.112(2.84) |
| G | 0.335(8.5) | 0.350(8.9) |
| H | 0.046(1.17) | 0.054(1.37) |
| I | 0.028(0.71) | 0.036(0.91) |
| J | 0.098(2.49) | 0.102(2.59) |
| K | 0.176(4.47) | 0.184(4.67) |
| L | 0.046(1.17) | 0.054(1.37) |
| M | 0.102(2.6) | 0.110(2.8) |
| N | 0.019(0.28) | 0.021(0.48) |
| ØP | 0.147(3.74) | 0.155(3.94) |


**Alternate**




| symbol | Dimensions in inches(millimeters) | |
|---|---|---|
| | Min | Max |
| A | 0.394(10.0) | 0.413(10.5) |
| B | 0.228(5.8) | 0.268(6.8) |
| C | 0.570(14.48) | 0.625(15.87) |
| D | 0.519(13.18) | 0.558(14.18) |
| E | 0.089(3.5) | 0.099(3.9) |
| F | 0.100(2.54) | 0.120(3.04) |
| G | 0.330(8.38) | 0.350(8.9) |
| H | 0.045(1.15) | 0.060(1.52) |
| I | 0.029(0.75) | 0.037(0.95) |
| J | 0.095(2.42) | 0.105(2.66) |
| K | 0.160(4.07) | 0.190(4.82) |
| L | 0.045(1.15) | 0.055(1.39) |
| M | 0.080(2.04) | 0.110(2.8) |
| N | 0.013(0.33) | 0.019(0.52) |
| ØP | 0.148(3.75) | 0.156(3.95) |

## ■ Mechanical data

- Epoxy : UL94-V0 rated flame retardant.
- Case : JEDEC TO-220AB molded plastic body.
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026.
- Polarity: As marked.
- Mounting Position : Any.
- Weight : Approximated 2.25 gram.




## ■ Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

| Parameter | Conditions | Symbol | C20L100CT | UNIT |
|---|---|---|---|---|
| Marking code | | | C20L100CT | |
| Peak repetitive reverse voltage<br>Working peak reverse voltage<br>DC blocking voltage | | $V_{RRM}$<br>$V_{RWM}$<br>$V_{RM}$ | 100 | V |
| Forward rectified current (total device) | | $I_O$ | 20 | A |
| Forward surge current (per diode) | 8.3ms single half sine-wave superimposed on rate load (JEDEC method) | $I_{FSM}$ | 200 | A |
| Operating and Storage temperature | | $T_J$, $T_{STG}$ | -40 ~ +150 | °C |

| Parameter | Conditions | Symbol | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|
| Forward voltage drop (per diode) | $I_F$ = 5A, $T_J$ = 25°C | $V_F$ | | 550 | | mV |
| | $I_F$ = 10A, $T_J$ = 25°C | | | 650 | 750 | |
| | $I_F$ = 5A, $T_J$ = 125°C | | | 500 | | |
| | $I_F$ = 10A, $T_J$ = 125°C | | | 580 | 680 | |
| Reverse current (per diode) | $V_R$ = 70V, $T_J$ = 25°C | $I_R$ | | 0.017 | | mA |
| | $V_R$ = 70V, $T_J$ = 125°C | | | 5.3 | | |
| | $V_R$ = 100V, $T_J$ = 25°C | | | | 0.1 | |
| | $V_R$ = 100V, $T_J$ = 125°C | | | 12 | 25 | |

Note : 1.Thermal resistance from junction to case per leg, with heatsink size(1.35" x 0.95" x 0.18") Al-plate.



Document ID : DS-11K9G
Revised Date : 2015/12/16
Revision : C9

■ Rating and characteristic curves

Fig. 1 - Instantaneous Forward Characteristics (per diode)





Fig. 2 - Reverse Characteristics (per diode)





Fig.3 - Forward Current Derating Curve (per diode)






Fig. 4 - Typical Junction Capacitance (per diode)






Document ID : DS-11K9G
Revised Date : 2015/12/16
Revision : C9

- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.

http://www.citcorp.com.tw/ Tel:886-3-5600628 Fax:886-3-5600636

Add:Rm. 3, 2F., No.32, Taiyuan St., Zhubei City, Hsinchu County 302, Taiwan (R.O.C.)



Document ID : DS-11K9G
Revised Date : 2015/12/16
Revision : C9