
WDescription


This N-channel MOSFETS use advanced trench technology and design to provide excellent RDS(on) with low gate charge. It can be used in a wide variety of applications.

Features

BVDSS	RDSON	ID
100V	0.16Ω	14A

1) Low gate charge.
2) Green device available.
3) Advanced high cell denity trench technology for ultra RDS(ON)
4) Excellent package for good heat dissipation.





TO-220

Absolute Maximum Ratings Tc=25℃,unless otherwise noted

Symbol	Parameter	Ratings	Units
VDS	Drain-Source Voltage	100	V
VGS	Gate-Source Voltage	±20	V
ID	Continuous Drain Current-1	14	A
	Continuous Drain Current-T=100℃	10	
	Pulsed Drain Current2	56	
EAS	Single Pulse Avalanche Energy3	8.8	mJ
PD	Power Dissipation4	88	W
TJ, TSTG	Operating and Storage Junction Temperature Range	-55 to +175	℃

Thermal Characteristics

Symbol	Parameter	Ratings	Units
$R_{\theta JC}$	Thermal Resistance ,Junction to Case1	62	℃/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient1	1.7	

Package Marking and Ordering Information

Part NO.	Marking	Package
KSM530	KSM530	TO-220

Electrical Characteristics T_C=25℃ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{DSS}	Drain-Sourtce Breakdown Voltage	V_{DS}=0V,I_D=250μA	100	—	—	v
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=0V, V_{DS}=32V	—	—	25	μA
I_{GSS}	Gate-Source Leakage Current	V_{DS}=±20V, V_{DS}=0A	—	—	±100	nA
On Characteristics						
$V_{GS(th)}$	GATE-Source Threshold Voltage	V_{DS}=VDS, I_D=250μA	2.0	—	4.0	V
$R_{DS(ON)}$	Drain-Source On Resistance[2]	V_{DS}=10V,I_D=6A	—	—	0.16	Ω
		V_{DS}=2.5V,I_D=5A	—	—	—	---
G_{FS}	Forward Transconductance	V_{DS}=5V,I_D=12A	5.1	—	—	S
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}=15V,V_{GS}=0V, f=1MHz	—	670	—	pF
C_{oss}	Output Capacitance		—	250	—	
C_{rss}	Reverse Transfer Capacitance		—	60	—	
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	V_{DS}=20V, V_{GS}=10V,R_{GEN}=3.3Ω	—	10	—	ns
t_r	Rise Time		—	34	—	ns
$t_{d(off)}$	Turn-Off Delay Time		—	23	—	ns
t_f	Fall Time		—	24	—	ns
Q_g	Total Gate Charge	V_{GS}=4.5V, V_{DS}=20V, I_D=6A	—	—	26	nC
Q_{gs}	Gate-SourceCharge		—	—	5.5	nC
Q_{gd}	Gate-Drain “Miller” Charge		—	—	11	nC
Drain-Source Diode Characteristics						
V_{SD}	Source-Drain Diode ForwardVoltage[2]	V_{GS}=0V,I_S =1A	—	—	2.5	V
t_{rr}	Reverse Recovery Time	I_F=7A,di/dt=100A/μS	—	150	280	ns
Q_{rr}	Reverse Recovery Charge		—	0.85	1.7	nC

Notes:

1. The data tested by surface mounted on a 1 inch² FR-4 board 2OZ copper.
2. The data tested by pulse width≤300us,duty cycle≤2%
3. The EAS data shows Max.rating.The test condition is V_{DD}=25v,V_{GS}=10V,L=0.1mH,i_{AS}=17.8A
4. The power dissipation is limited by 150℃ junction temperature.

Typical Characteristics T_J=25℃ unless otherwise noted




Fig. 1 Typical Output Characteristics, TC = 25 °




Fig. 2 Typical Transfer Characteristics




Fig. 3 Typical Output Characteristics, TC = 175°C




Fig. 4 - Normalized On-Resistance vs. Temperature




Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage




Fig. 6 - Typical Source-Drain Diode Forward Voltage




Fig. 7 - Typical Gate Charge vs. Gate-to-Source Voltage




Fig. 8 - Maximum Safe Operating Area




Fig. 9 - Maximum Effective Transient Thermal Impedance, Junction-to-Case