


NOTE:  
 1. Rating: AC125V 5A/250V 3A  
 2. Operating force: 25±10gf  
 3. Mechanical Life: 1,000,000  
 3. Electrical Life: 6000-10,000



Circuit Diagram

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
⑧	Shrapnel 2	—	1	Copper Alloy	—	—
⑦	Shrapnel 1	—	1	Beryllium Copper	—	—
⑥	Contact	—	1	Copper Alloy	Plating silver	—
⑤	Lever	—	1	Stainless Steel	—	—
④	Terminal	—	3	Copper Alloy	Plating silver	—
③	Housing	—	1	PBT	Black	—
②	Knob	—	1	PBT	Black	—
①	Cover	—	1	PBT	Black	—

APPROVALS		DATE	TITLE:
DRAWN	J.X.Zhang	2014/8/20	MICRO SWITCHS

APPROVALS		PART NO.
CHECKED	—	K9-1910D

APPROVALS		SCALE:
TOLERANCES ARE	±0.30	1:1
10~20	±0.25	—
5~10	±0.20	—
~ 5	±0.20	—

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	DRAWING NO.	SHEET
—	A	—	NEW	—	—	—	—	1 OF 1



ELECTRONICS CO., LTD

MICRO SWITCHS

K9-1910D

SCALE: 1:1

DRAWING NO. SHEET 1 OF 1