

TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB FLOATING-POINT DIGITAL SIGNAL PROCESSOR KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

- Commercial Operating Free-Air Temperature Range
–0°C to 70°C
- Military Operating Free-Air Temperature Range
–55°C to 125°C, QML Processing
- Fast Instruction Cycle Time of 50 ns
- Two 1K × 32-Bit Single-Cycle Dual-Access On-Chip RAM Blocks
- 32-Bit Instruction and Data Words, 24-Bit Addresses
- Integer, Floating-Point, and Logical Operations
- 40- or 32-Bit Floating-Point/Integer Multiplier and Arithmetic Logic Unit (ALU)
- 24 × 24-Bit Integer Multiplier, 32-Bit Product
- 32 × 32-Bit Floating-Point Multiplier, 40-Bit Product
- Parallel ALU and Multiplier Execution in a Single Cycle
- 32-Bit Barrel Shifter
- Eight Extended-Precision Registers (Accumulators)
- Circular and Bit-Reversed Addressing Capabilities
- One Independent Bidirectional Serial Port With Support for 8-, 16-, 24-, or 32-Bit Transfers
- Two 32-Bit Timers With Control and Counter Registers
- Validated Ada Compiler
- 64-Word × 32-Bit Instruction Cache
- On-Chip Direct Memory Access (DMA) Controller for Concurrent I/O and CPU Operation
- Flexible Boot Program Loader for the '320C31KGDB Instead of the ROM
- One 32-Bit External Port for the '320C31KGDB (24-Bit Address)
- Two Address Generators With Eight Auxiliary Registers and Two Auxiliary Register Arithmetic Units (ARAUs)
- Zero-Overhead Loops With Single-Cycle Branches
- Interlocked Instructions for Multiprocessing Support
- Two- and Three-Operand Instructions
- Conditional Calls and Returns
- Block Repeat Capability
- Fabricated Using Enhanced Performance Implanted CMOS (EPIC™) Technology by Texas Instruments

description

The TMP/SMJ320C31KGDB and SMJ320LC31KGDB digital signal processors (DSPs) known good dies (KGDs) are high-performance, 32-bit floating-point processors manufactured in 0.72-μm, double-level metal CMOS technology.

The TMP/SMJ320C31KGDB and SMJ320LC31KGDB internal busing and special digital signal processing instruction set have the speed and flexibility to execute up to 40 million floating-point operations per second (MFLOPS). The devices optimize speed by implementing functions in hardware that other processors implement through software or microcode. This hardware-intensive approach provides performance previously unavailable on a single chip.

The devices can perform parallel multiply and ALU operations on integer or floating-point data in a single cycle. Each processor also possesses a general-purpose register file, a program cache, dedicated ARAUs, internal dual-access memories, one DMA channel supporting concurrent I/O, and a short machine-cycle time. High performance and ease of use are results of these features.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

EPIC is a trademark of Texas Instruments Incorporated.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 1443 • HOUSTON, TEXAS 77251-1443

Copyright © 2001, Texas Instruments Incorporated
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB FLOATING-POINT DIGITAL SIGNAL PROCESSOR KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

description (continued)

The large address space, multiprocessor interface, internally and externally generated wait states, one external interface port, two timers, one serial port, and multiple interrupt structure enhance general-purpose applications. The TMP320C31KGDB and the SMJ320C31KGDB support a wide variety of system applications from host processor to dedicated coprocessor.

High-level language support is implemented through a register-based architecture, large address space, and the device's ability to execute 40 million floating-point operations per second (MFLOPS) and perform parallel multiple and ALU operations.

For additional information when designing for cold temperature operation, please see Texas Instruments application report *320C3x, 320C4x and 320MCM42x Power-up Sensitivity at Cold Temperature*, literature number SGUA001.

known good die (KGD) technology

KGD options are available for use in multichip modules and chip-on-board (COB) applications. The current verification technology that supports KGD requirements for the TMP320C31KGDB, SMJ320C31KGDB, and the SMJ320LC31KGDB is a removable tab (R-Tab).

The availability of selected DSP products in a tape-automated bond (TAB) configuration has made possible the use of an R-Tab technique. The TAB leadframe is attached to gold-bumped die using nonoptimal bonding parameters. This technique allows easy removal of the die after all the needed screens and parametric tests are complete. The tape is removed from the tested part and the die is shipped in a conventional die container. The gold bumps remain on the bond pads that provide for subsequent attachment of gold-ball bonds.

Future implementations may have only aluminum bond pads. Please contact factory for current information.

electrical specifications

For military electrical and timing specifications, please see the *SMJ320C31, SMJ320LC31, SMQ320LC31 Digital Signal Processors* data sheet, literature number SGUS026. For commercial specifications, see the *TMS320C31, TMS320LC31 Digital Signal Processors* data sheet, literature number SPRS035.




Figure 1. Device Nomenclature



JEDEC STANDARD


- Die thickness is approximately 15 mils $\pm$ 1 mil.
- Backside surface finish is silicon.
- Maximum allowable die junction operating temperature is 175°C.
- Glassivation material is compressive nitride.
- Bond pad metal is composed of copper-doped aluminum.
- Percentage of defect allowed for burned-in die is 5%.
- Life test data is available.
- Configuration control notification.
- Group A attribute summary is available (SMJ only).
- Suggested die-attach material is silver glass (QMI 2569F).
- Suggested bond wire size is 1.25 mils.
- Suggested bonding method is gold-ball bonding.
- ESD rating is Class II.
- Maximum allowable peak process temperature for die attach is 440°C $\pm$ 5°C (for QMI 2569F).
- Saw kerf is dependent on blade size used.
- Die backside potential is grounded.

TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB FLOATING-POINT DIGITAL SIGNAL PROCESSOR KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

TMP/SMJ320C31KGDB (rev 6.1) known good die pad information

Figure 2 shows the TMP/SMJ320C31KGDB die-numbering format. See Table 1 for TMP/SMJ320C31KGDB die pad information.



**Figure 2. '320C31KGD Die Numbering Format
(See Table 1)**

Table 1 provides a reference for the following:

- The 'C31 signal identities in relation to the pad numbers.
- The 'C31 X,Y coordinates, where bond pad 1 serves as the origin (0,0).

In addition, significant specifications include:

- X,Y coordinate data is in microns (μm).
- Coordinate origin is at (0,0) (center of bond pad 1).
- Average pitch is $202 \mu\text{m}$ (7.95 mils).
- The active silicon dimensions are $7889.0 \mu\text{m} \times 7353.25 \mu\text{m}$ (311 mils $\times$ 289 mils).
- The approximate diced silicon dimensions (active + cut scribe street) are $8051.8 \mu\text{m} \times 7518.4 \mu\text{m}$ (317 mils $\times$ 296 mils).
- Bond pad dimensions are $103.50 \mu\text{m} \times 103.50 \mu\text{m}$ (4.07 mils $\times$ 4.07 mils).
- Center of bond pad to edge of die ranges from $170 \mu\text{m}$ – $213 \mu\text{m}$ (6.7 mils–8.4 mils). The range of $43 \mu\text{m}$ exists since the dicing process results in some tolerance. Due to the consistency and precision of the bond pad locations in reference to each other, the center of bond pad 1 was chosen as the origin.

TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB FLOATING-POINT DIGITAL SIGNAL PROCESSOR KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

Table 1. '320C31KGD Die Pad/TAB Lead Information : rev 6.1 (0,72 μm)

DIE SIDE #1				
C31 DIE BOND PAD LOCATIONS	DIE/TAB BOND PAD IDENTITY	X-COORDINATE OF THE DIE BOND PAD (μm)	Y-COORDINATE OF THE DIE BOND PAD (μm)	PITCH OF LEAD (#,# REFERENCES WHICH DIE BONDS) (μm)
1	A9	0.00	0.00	224.46 (1, 2)
2	DVSS		-224.46	201.78 (2, 3)
3	A8		-426.24	224.46 (3, 4)
4	A7		-650.70	224.46 (4, 5)
5	A6		-875.16	224.46 (5, 6)
6	A5		-1099.62	202.86 (6, 7)
7	AVDD		-1302.48	201.78 (7, 8)
8	A4		-1504.26	224.46 (8, 9)
9	A3		-1728.72	224.46 (9, 10)
10	A2		-1953.18	224.46 (10, 11)
11	A1		-2177.64	224.46 (11, 12)
12	A0		-2402.10	202.86 (12, 13)
13	CVSS		-2604.96	223.38 (13, 14)
14	D31		-2828.34	271.98 (14, 15)
15	VDDL		-3100.32	162.36 (15, 16)
16	VDDL		-3262.68	200.52 (16, 17)
17	D30		-3463.20	207.18 (17, 18)
18	VSSL		-3670.38	162.36 (18, 19)
19	VSSL		-3832.74	178.92 (19, 20)
20	DVSS		-4011.66	244.98 (20, 21)
21	D29		-4256.64	224.46 (21, 22)
22	D28		-4481.10	188.46 (22, 23)
23	DVDD		-4669.56	280.98 (23, 24)
24	D27		-4950.54	202.86 (24, 25)
25	IVSS		-5153.40	180.18 (25, 26)
26	D26		-5333.58	202.86 (26, 27)
27	D25		-5536.44	202.86 (27, 28)
28	D24		-5739.30	202.86 (28, 29)
29	D23		-5942.16	202.86 (29, 30)
30	D22		-6145.02	202.86 (30, 31)
31	D21		-6347.88	174.60 (31, 32)
32	DVDD		-6522.48	172.98 (32, 33)
33	D20		-6695.46	



TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB
FLOATING-POINT DIGITAL SIGNAL PROCESSOR
KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

Table 1.'320C31KGD Die Pad/TAB Lead Information : rev 6.1 (0,72 μm) (continued)

DIE SIDE #2				
C31 DIE BOND PAD LOCATIONS	DIE/TAB BOND PAD IDENTITY	X-COORDINATE OF THE DIE BOND PAD (μm)	Y-COORDINATE OF THE DIE BOND PAD (μm)	PITCH OF LEAD (#,# REFERENCES WHICH DIE BONDS) (μm)
34	DVSS	396.72	-7219.80	180.72 (34, 35)
35	D19	577.44		202.86 (35, 36)
36	D18	780.30		210.06 (36, 37)
37	D17	990.36		210.06 (37, 38)
38	D16	1200.42		210.06 (38, 39)
39	D15	1410.48		188.46 (39, 40)
40	CVSS	1598.94		187.38 (40, 41)
41	D14	1786.32		188.46 (41, 42)
42	DVDD	1974.78		187.38 (42, 43)
43	D13	2162.16		188.46 (43, 44)
44	IVSS	2350.62		187.38 (44, 45)
45	D12	2538.00		210.06 (45, 46)
46	D11	2748.06		210.06 (46, 47)
47	D10	2958.12		192.78 (47, 48)
48	VDDL	3150.90		162.36 (48, 49)
49	VDDL	3313.26		186.12 (49, 50)
50	D9	3499.38		210.06 (50, 51)
51	D8	3709.44		188.46 (51, 52)
52	DVSS	3897.90		170.10 (52, 53)
53	VSSL	4068.00		162.36 (53, 54)
54	VSSL	4230.36		186.12 (54, 55)
55	D7	4416.48		210.06 (55, 56)
56	D6	4626.54		188.46 (56, 57)
57	DVDD	4815.00		187.38 (57, 58)
58	D5	5002.38		210.06 (58, 59)
59	D4	5212.44		210.06 (59, 60)
60	D3	5422.50		210.06 (60, 61)
61	D2	5632.56		210.06 (61, 62)
62	D1	5842.62		210.06 (62, 63)
63	D0	6052.68		210.06 (63, 64)
64	H1	6262.74		210.06 (64, 65)
65	H3	6472.80		174.06 (65, 66)
66	DVDD	6646.86		

TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB
FLOATING-POINT DIGITAL SIGNAL PROCESSOR
KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

Table 1.'320C31KGD Die Pad/TAB Lead Information : rev 6.1 (0,72 μ m) (continued)

DIE SIDE #3				
C31 DIE BOND PAD LOCATIONS	DIE/TAB BOND PAD IDENTITY	X-COORDINATE OF THE DIE BOND PAD (μ m)	Y-COORDINATE OF THE DIE BOND PAD (μ m)	PITCH OF LEAD (#,# REFERENCES WHICH DIE BONDS) (μ m)
67	DVSS	7136.64	-6714.54	158.58 (67, 68)
68	CVSS		-6555.96	153.54 (68, 69)
69	IVSS		-6402.42	160.56 (69, 70)
70	X2		-6241.86	169.56 (70, 71)
71	X1		-6072.30	292.14 (71, 72)
72	HOLDA		-5780.16	205.56 (72, 73)
73	HOLD		-5574.60	181.98 (73, 74)
74	CVDD		-5392.62	276.48 (74, 75)
75	RDY		-5116.14	217.98 (75, 76)
76	STRB		-4898.16	224.46 (76, 77)
77	R/W		-4673.70	219.96 (77, 78)
78	RESET		-4453.74	217.98 (78, 79)
79	XF0		-4235.76	202.86 (79, 80)
80	CVDD		-4032.90	223.38 (80, 81)
81	XF1		-3809.52	224.46 (81, 82)
82	IACK		-3585.06	219.96 (82, 83)
83	INT0		-3365.10	196.38 (83, 84)
84	DVSS		-3168.72	180.18 (84, 85)
85	VSSL		-2988.54	197.28 (85, 86)
86	INT1		-2791.26	200.70 (86, 87)
87	VDDL		-2590.56	162.36 (87, 88)
88	VDDL		-2428.20	196.02 (88, 89)
89	INT2		-2232.18	213.48 (89, 90)
90	INT3		-2018.70	268.38 (90, 91)
91	DR0		-1750.32	202.86 (91, 92)
92	CVSS		-1547.46	201.78 (92, 93)
93	FSR0		-1345.68	224.46 (93, 94)
94	CLKR0		-1121.22	224.46 (94, 95)
95	CLKX0		-896.76	202.86 (95, 96)
96	IVSS		-693.90	201.78 (96, 97)
97	FSX0		-492.12	202.86 (97, 98)
98	PVDD		-289.26	273.78 (98, 99)
99	DX0		-15.48	



TMP320C31KGDB, SMJ320C31KGDB, SMJ320LC31KGDB
FLOATING-POINT DIGITAL SIGNAL PROCESSOR
KNOWN GOOD DIES

SGUS023B – APRIL 1997 – REVISED OCTOBER 2001

Table 1.'320C31KGD Die Pad/TAB Lead Information : rev 6.1 (0,72 μm) (continued)

DIE SIDE #4				
C31 DIE BOND PAD LOCATIONS	DIE/TAB BOND PAD IDENTITY	X-COORDINATE OF THE DIE BOND PAD (μm)	Y-COORDINATE OF THE DIE BOND PAD (μm)	PITCH OF LEAD (#,# REFERENCES WHICH DIE BONDS) (μm)
100	V _{SUBS} [†]	6705.00	452.52	224.10 (100, 101)
101	SHZ	6480.90		181.98 (101, 102)
102	DV _{SS}	6298.92		172.98 (102, 103)
103	TCLK0	6125.94		174.06 (103, 104)
104	PV _{DD}	5951.88		230.58 (104, 105)
105	TCLK1	5721.30		282.06 (105, 106)
106	EMU3	5439.24		191.16 (106, 107)
107	EMU0	5248.08		184.68 (107, 108)
108	EMU1	5063.40		184.68 (108, 109)
109	EMU2	4878.72		184.68 (109, 110)
110	MCMP	4694.04		167.58 (110, 111)
111	CV _{SS}	4526.46		201.78 (111, 112)
112	A23	4324.68		195.66 (112, 113)
113	A22	4129.02		266.40 (113, 114)
114	V _{DDL}	3862.62		162.36 (114, 115)
115	V _{DDL}	3700.26		278.28 (115, 116)
116	A21	3421.98		195.48 (116, 117)
117	A20	3226.50		174.06 (117, 118)
118	V _{SSL}	3052.44		151.38 (118, 119)
119	DV _{SS}	2901.06		172.98 (119, 120)
120	A19	2728.08		174.06 (120, 121)
121	AV _{DD}	2554.02		172.98 (121, 122)
122	A18	2381.04		195.66 (122, 123)
123	A17	2185.38		195.66 (123, 124)
124	A16	1989.72		195.66 (124, 125)
125	A15	1794.06		195.66 (125, 126)
126	A14	1598.40		282.06 (126, 127)
127	A13	1316.34		195.66 (127, 128)
128	A12	1120.68		195.66 (128, 129)
129	A11	925.02		174.06 (129, 130)
130	AV _{DD}	750.96		172.98 (130, 131)
131	A10	577.98		174.06 (131, 132)
132	CV _{SS}	403.92		

[†] V_{SUBS} connects to die metallization. Tie this pin to clean ground.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2008, Texas Instruments Incorporated