



Recommended P.C.B Layout(Top Side)
P.C.B Thickness = 1.20-1.60mm
(Tolerance=±0.05)



X2510 W R S-04 - 9T SN

- ① ②③ ④⑤ ⑥ ⑦

- ① Series No. W-WAFER
- ② Category: R-Right Angle 90°
- ③ Welding Board Angle: S-SMT
- ④ Welding Way: XX-Single row
- ⑤ Row No.-Pin No. 9T-PA9T UL94-V0
- ⑥ Material: SN-Bright tin plating 70-120u"
- ⑦ Planting Category

Specifications:

规格:

Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating: 4.0A
 额定电流: 4.0A
 Withstanding voltage: 1000V AC/minute
 耐压电压: 1000V AC/minute
 Temperature range: -25℃~+85℃
 温度范围: -25℃~+85℃
 Insulation resistance: ≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance: ≤0.02Ω
 接触电阻: ≤0.02Ω

Poles	Dimensions(mm)			
	A	B	C	D
2	7.62	2.54	-	-
3	-	-	-	-
4	12.70	7.62	-	-
5	15.24	10.16	-	-
6	-	-	-	-
7	-	-	-	-
8	-	-	-	-
9	-	-	-	-

X2510WRS-XX-9TSN	PA9T UL 94V-0	Brass	Tin Plating Fog	X2510H
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With XKB Housing

REVISIONS					UNSPECIFIED TOLERANCES			XKB INDUSTRIAL PRECISION CO.,LIMITED		
ΔX					ANGLAR	±5°	DSND	DATE	SCALE: N/A	MODEL TYPE:
ΔX					L ≤ 4	±0.2	DWN	DATE	VIEW:	PART NO.:
ΔX					4 < L ≤ 16	±0.3	CHKD	DATE	UNIT: mm/in	2.54 mm Crimp Style Connectors
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16 < L ≤ 63	±0.4	APPD	DATE	SIZE: A4	DWG NO.:
					L > 63	±0.5				X2510WRS-XX-9TSN
										WEIGHT
										1.0g
										SHEET
										1/1
										REVISION
										A0